



Figure similar

Article No. : 6FC5317-4AA00-0AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

| | |
|-------------------------|---------|
| Input voltage | DC 24 V |
| Power consumption, max. | 315 W |
| Power loss | 16 W |

Working memory

| | |
|-----------------|-----------------------------|
| Memory capacity | 4 Gbyte DRAM 1 Gbyte NVM |
|-----------------|-----------------------------|

Mechanical data

| | |
|----------------------|-------------------|
| Degree of protection | IP20 |
| Net weight | 2.4 kg (5.29 lb) |
| Width | 50 mm (1.97 in) |
| Height | 300 mm (11.81 in) |
| Depth | 270 mm (10.62 in) |

Ambient conditions

Climate class according to EN60721-3-3: Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

| | |
|-----------|--------------------------------|
| Operation | 0 ... 55 °C (32 ... 131 °F) |
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
| Storage | -25 ... 55 °C (-13 ... 131 °F) |

Relative humidity

| | |
|-----------|------------|
| Operation | 5 ... 95 % |
| Storage | 5 ... 95 % |
| Transport | 5 ... 95 % |

Approvals

Certificate of suitability: CE, cULus, UKCA, EAC, RCM