

Article No. : 6FC5317-4AA00-1DA0



Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Figure similar

### Rated data

Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	98 W

### Mechanical data

Mounting position	Horizontal
Operator panel	Perpendicular
Net weight	7.30 kg (16.09 lb)
Width	464.0 mm (18.26 in)
Height	294.0 mm (11.57 in)
Depth	138.0 mm (5.43 in)

### Degree of protection

Front side	IP65
Rear side	IP20 / UL open type

### General tech. specifications

Mains buffering time	3 ms, 20 ms mit SITOP smart power supply
----------------------	--

### Ambient conditions

#### Ambient temperature

Operation on the front	0 ... 40 °C (32 ... 104 °F)
Operation at the rear	0 ... 45 °C (32 ... 113 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Transport	-20 ... 70 °C (-4 ... 158 °F)

#### Relative humidity

Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

### Approvals

Certificate of suitability	CE, cULus, EAC, KC, RCM
----------------------------	-------------------------