

Data sheet for SINUMERIK 808D PPU 160.3

Article No. : 6FC5370-2BT03-0AA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	50 W

Mechanical data

Mounting position	Vertical
Operator panel	Perpendicular
Net weight	2.90 kg (6.39 lb)
Width	265.0 mm (10.43 in)
Height	330.0 mm (12.99 in)
Depth	104.0 mm (4.09 in)

Degree of protection

Front side	IP65 With the front flap closed
Rear side	IP20 / UL open type

Panel cutout

Width	244.1 mm (9.61 in)
Height	307.1 mm (12.09 in)

General tech. specifications

Mains buffering time	3 ms, 20 ms mit SITOP smart power supply
----------------------	--

Ambient conditions

Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 50 °C (32 ... 122 °F)
Storage	-20 ... 60 °C (-4 ... 140 °F)
Transport	-20 ... 60 °C (-4 ... 140 °F)

Relative humidity

Operation	5 ... 90 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals

Certificate of suitability	CE, EAC, KC
----------------------------	-------------