

## Data sheet for SINUMERIK 828 PPU 290.4

Article No. : 6FC5370-8AA40-0BA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	60 W

### Mechanical data

Mounting position	Vertical
Operator panel	Vertical
Net weight	8.90 kg (19.62 lb)
Width	416.0 mm (16.38 in)
Height	470.0 mm (18.50 in)
Depth	105.0 mm (4.13 in)

### Degree of protection

Front side	IP65
Rear side	IP20 / UL open type

### General tech. specifications

Mains buffering time	3 ms, 20 ms mit SITOP smart power supply
----------------------	--

### Ambient conditions

#### Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Transport	-20 ... 60 °C (-4 ... 140 °F)

#### Relative humidity

Operation	5 ... 90 %
Storage	10 ... 100 %
Transport	5 ... 95 %

### Approvals

Certificate of suitability	CE, cULus, EAC
----------------------------	----------------