

## Data sheet for Incremental encoder

Article No. : 6FX2001-4NB00



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data

Operating voltage $U_p$	DC 10 ...30 V
Max. power consumption without load	150 mA
Signal level	UH $\geq$ 21 V at IH = 20 mA at 24 V; UL $\leq$ 2,8 V at IL = 20 mA at 24 V
Resolution	1,000 S/R
Accuracy	65 rad
Sampling frequency, max.	300 kHz
Switching time (10 ... 90 %)	$\leq$ 200 ns Rise / fall time $t_{+/-} \leq$
Phase relation signal A to B	90 °
Edge clearance at 300 kHz	0.45 $\mu$ s
LED failure monitoring	High impedance driver

### Cable length

To the downstream electronics, max. 300 m

### Ambient temp in operation

#### Fixed installation of flange outlet or cable

- At  $U_p = 10V \dots 30V$  -40 ... 100 °C

#### Flexible cable

- At  $U_p = 10V \dots 30V$  -10 ... 100 °C

### Standards

Compliance with standards	CE, cULus
EMC class filter	Tested according to the EMC guidelines 89/336/EEC and the rules of the EMC guidelines (generic standards)

### Mechanical data

Shaft diameter	10 mm
Shaft length	20 mm
Angular acceleration, max.	100,000 rad/s <sup>2</sup>
Rotor moment of inertia	0.00000145 kgm <sup>2</sup>
Vibration (55...2000 Hz), max.	300 m/s <sup>2</sup>
Friction torque (at 20°C)	0.01 Nm
Starting torque (at 20°C)	0.01 Nm
Net weight	0.3 kg

### Max. admissible speed

Electrical	18,000 rpm
Mechanical	12,000 rpm

### Load capacity

#### n $\leq$ 6000 rpm

- Axial	40 N
- Radial at shaft end	60 N

#### n > 6000 rpm

- Axial	10 N
- Radial at shaft end	20 N

### Shock, max.

2 ms	2,000 m/s <sup>2</sup>
6 ms	1,000 m/s <sup>2</sup>

### Degree of protection

At housing	IP67
At shaft input	IP64