



Figure similar

Data sheet for MOTION CONNECT 350 / 380

Article No. : 6FX3502-7CD01-1BF0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Electrical data

| | |
|---|-----------------------------|
| No. of cores x cross-section mm ² | 4 x 0.75 / 3 x 2 x 0.25 |
| Test voltage, rms Power conductors | Power: 4.0 kV Encoder: 500V |
| Holding brake | No |
| Rated voltage U0/U in accordance with EN 50395 Power conductors | 1000 V/30 V |

Mechanical data

| | |
|---|--|
| Smallest bending radius (fixed installation) | 4 x Cable outer diameter |
| Smallest bending radius (flexible installation) | 7.5 x Cable outer diameter |
| Number of bends, max. | 1,000,000 |
| Tensile stress, max. Fixed installation | 50 N/mm ² (7252 lbf/in ²) |
| Tensile stress, max. Flexible installation | 20 N/mm ² (2901 lbf/in ²) |
| Torsional stress | Absolute 30°/m |
| Connection type | Hybrid connector (Cable outlet DE) |
| Length | 15.0 m |
| Weight (without connector) | 1.3 kg |

Technical data

Ambient temperature

| | |
|---|---------------------------------|
| Operation with permanently installed cable | -20 ... 80.0 °C |
| Kind of connection cable | Dual cable connection |
| Material of the cable sheath | PVC |
| Type of insulation | CFC/silicone-free |
| Standard for behavior in fire: flame resistance | EN 60332-1-1 to 1-3 |
| Oil resistance | EN 60811-2-1 (mineral oil only) |
| Verification of suitability, CE marking | Yes |
| Verification of suitability, UL approval | Yes |
| Verification of suitability, RoHS conformity | Yes |