



Figure similar
«I2_MC_Abbildung»

MOTION CONNECT 500

Article No. : 6FX5008-1BA11-6AA0

«I2_MC_Artikel_Nr»

Client order no. : «I2_SD_Label_KAUFTRAGNR»	«I2_LZ»	Item no. : «I2_SD_Label_ITEMNR»	«I2_LZ»
Order no. : «I2_SD_Label_SAUFRAGNR»	«I2_LZ»	Consignment no. : «I2_SD_Label_KOMMISSIONSNR»	«I2_LZ»
Offer no. : «I2_SD_Label_ANGEBOT»	«I2_LZ»	Project : «I2_SD_Label_PROJEKT»	«I2_LZ»
Remarks : «I2_SD_Label_BEMERKUNG»	«I2_LZ»		

Electrical data

«I2_electricdata»

No. of cores x cross-section mm ² «I2_MC_Anzahl_Adern_Querschnitt»	4x1.5 + 2x1.5C C
Test voltage, rms Power conductors «I2_MC_Pruefspannung_Versorgungsadern_Eff»	4.0 kV
Test voltage, rms Signal conductors «I2_MC_Label_Anschluss_Haltebremse»	2.0 kV
Type with braking lead «I2_MC_Label_Anschluss_Haltebremse»	Yes «I2_PMD_ABY153»
Rated voltage V0/V according to EN 50395 «I2_MC_Label_Anschluss_Haltebremse»	600 V/1000 V

Mechanical data

«I2_mechanicalData»

Type of connection cable engine side «I2_MC_Minimaler_Biegeradius_fester_Verle»	n/a (sold by the meter) «I2_PMD_ABY153»
Connector size «I2_PMD_ABY155_001_000»	n/a (sold by the meter) «I2_PMD_ABY155»
Type of bolting «I2_MC_Anzahl_Biegungen_max»	n/a (sold by the meter) «I2_PMD_ABY155»
Type of connection cable converter side «I2_PMD_ACB333_001_000»	n/a (sold by the meter) «I2_PMD_ABY155»
Maximum cable outer diameter «I2_PMD_ACB334_001_000»	10.8 mm
Length «I2_MC_Torsionsbelastung»	500.0 m
Weight (without connector) «I2_ENC_anschlussstyp»	110.0 kg
Static deployment «I2_ENC_anschlussstyp»	
Smallest bending radius (fixed installation) «I2_ENC_anschlussstyp»	27.0 mm
Tensile load for permanently installed cable, max. «I2_ENC_anschlussstyp»	50 N/mm ² (7252 lbf/in ²)
Torsional stress «I2_ENC_anschlussstyp»	Absolute 30°/m «I2_PMD_ABY153»
Dynamic deployment «I2_ENC_anschlussstyp»	
Smallest bending radius(flexible installation in a cable carriers) «I2_ENC_anschlussstyp»	195.0 mm
Acceleration horizontal, max «I2_ENC_anschlussstyp»	2.0 m/s ²
Maximum traversing velocity «I2_ENC_anschlussstyp»	30.0 m/min
Travel path «I2_ENC_anschlussstyp»	5 m
Number of bends, max. «I2_ENC_anschlussstyp»	100,000
Tensile load for moving cable, max. «I2_ENC_anschlussstyp»	20 N/mm ² (2901 lbf/in ²)

MOTION CONNECT 500

Article No. : 6FX5008-1BA11-6AA0

«I2_MC_Artikel_Nr»

Technical data

«I2_technicaldata»

Ambient temperature

«I2_h_umgebung_umgebungtemp»

Operation with permanently installed cable
«I2_MC_Betrieb_feste_Leitung»

-20.0 ... 80.0 °C
Module-end power connector 0 ... 55°C
«I2_PMD_ABY148»

Operation with moving cable
«I2_MC_Betrieb_feste_Leitung»

0.0 ... 60.0 °C
Module-end power connector 0 ... 55°C
«I2_PMD_ABY148»

Storage
«I2_MC_Betrieb_feste_Leitung»

-20.0 ... 80.0 °C
Module-end power connector -20 ... 70°C
«I2_PMD_ABY148»

Kind of connection cable
«I2_MC_Art_Leitung»

Sold by the meter
«I2_PMD_ABY148»

Material of the cable sheath
«I2_MC_Material_Kabelmantel»

PVC DESINA color orange RAL 2003
«I2_PMD_AAC618»

Type of insulation
«I2_MC_Art_Isolierung»

CFC/silicone-free
«I2_UI_AAB047»

Standard for behavior in fire: flame resistance
«I2_MC_Norm_Brandverhalten_Flammwidrigkei»

EN 60332-1-1 to 1-3
«I2_PMD_ABT887»

Oil resistance
«I2_MC_Oelbestaendigkeit_Kabel»

EN 60811-2-1 (mineral oil only)
«I2_PMD_ACB330»

Verification of suitability as authorisation for USA
«I2_MC_Eignungsnachweis_CE»

UL758

Verification of suitability as authorisation for Canada
«I2_MC_Eignungsnachweis_UL»

CSA-C22.2-N.210.2-M90