



Figure similar

## MOTION CONNECT 800PLUS

Article No. : 6FX8002-2DC46-1HA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data

|   |                          |
|---|--------------------------|
| Design of the sensor  | Motor encoder DRIVE-CLiQ |
| Test voltage, rms Signal conductors                             | 500 V                    |
| Rated voltage U0/U in accordance with EN 50395 Power conductors | 30 V                     |

### Mechanical data

|   |                      |
|---|----------------------|
| Type of connection cable engine side            | M12 full thread      |
| Type of connection cable converter side         | M17                  |
| Maximum cable outer diameter                    | 7.1 mm               |
| Smallest bending radius (fixed installation)    | 35 mm                |
| Smallest bending radius (flexible installation) | 75 mm                |
| Number of bends, max.                           | 10,000,000           |
| Maximum traversing velocity                     | 300 m/min            |
| Acceleration horizontal, max                    | 50 m/s <sup>2</sup>  |
| Tensile stress, max. Fixed installation         | 50 N/mm <sup>2</sup> |
| Tensile stress, max. Flexible installation      | 20 N/mm <sup>2</sup> |
| Torsional stress                                | Absolute 30°/m       |
| Length  | 70.0 m               |

### Technical data

#### Ambient temperature

|   |  |
|---|--|
| Operation with permanently installed cable              | -50 ... 80 °C<br>Module- and motor-side RJ45 plug -20°C ... 80°C,<br>M17 plug -20 ... 80°C |
| Operation with moving cable                             | -20 ... 60 °C  |
| Storage   | -20 ... 80 °C<br>Module- and motor-side RJ45 plug -20°C ... 80°C,<br>M17 plug -20 ... 80°C |
| Kind of connection cable                                | Basis cable  |
| Material of the cable sheath                            | PUR, HD22.10 S2 (VDE 0282, part 10) DESINA-<br>color green RAL 6018                        |
| Type of insulation                                      | without CFC and silicone IEC 60754-1/DIN VDE<br>0472-815                                   |
| Standard for behavior in fire: flame resistance         | EN 60332-1-1 to 1-3  |
| Oil resistance  | EN 60811-2-1   |
| Verification of suitability as authorisation for USA    | UL STYLE 2502  |
| Verification of suitability as authorisation for Canada | CSA-N.210.2-M90  |