

PS2 keyboard 19", en, with touch pad, built-in keyboard for devices with corresponding interface, scope of supply: 1 keyboard



Figure similar

| General information | |
|--|---|
| Product type designation | PS/2 built-in keyboard INT |
| Control elements | |
| Keyboard fonts | |
| <ul style="list-style-type: none"> • Design • Keyboard assignment • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys — Programmable • Number pad • status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys | Membrane keyboard B3F, 101/102 or 104/105 OMRON No 12 Yes Yes Yes; Num, Caps and Scroll Yes Yes |
| Connection type | |
| <ul style="list-style-type: none"> • USB • PS/2 | Yes; With PS/2 USB adapter (not included in the scope of supply) Yes |
| Frame size/design | |
| <ul style="list-style-type: none"> • Standard • 19" keyboard | Yes; For industrial applications Yes |
| Installation type/mounting | |
| Rack mounting | No; Built-in keyboard, 19" rack |
| Input current | |
| Current consumption (rated value) | 25 mA; Typical |
| Battery | |
| Battery-operated | No; maintenance-free |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| <ul style="list-style-type: none"> • Limit class A, for use in industrial areas | Yes |
| Degree and class of protection | |
| IP (at the front) | IP65 |
| IP (rear) | IP20 |
| Splashproof | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| RoHS conformity | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |

| | | |
|--|---|-----------------------|
| • min. | 0 °C | |
| • max. | 40 °C | |
| Ambient temperature during storage/transportation | | |
| • min. | -10 °C | |
| • max. | 50 °C | |
| Relative humidity | | |
| • Operation, max. | 90 %; no condensation | |
| • Condensation permissible | No | |
| Operating systems | | |
| Runs under operating system | | |
| • Windows CE | Yes | |
| • Windows Vista | Yes | |
| • Windows XP | Yes | |
| • Windows 7 | Yes | |
| • Windows 10 | Yes | |
| Mechanics/material | | |
| Material | | |
| • Sheet steel | Yes | |
| Enclosure material (front) | | |
| • Plastic | Yes; AUTOTEX (R) V150 | |
| Service life | | |
| • Number of operating cycles, keys | 1 000 000; Operations (minimum) | |
| Dimensions | | |
| Width | 482.6 mm | |
| Height | 42.5 mm | |
| Depth | 177.8 mm | |
| Weights | | |
| Weight (without packaging) | 1 480 g | |
| Weight (with packaging) | 1 665 g | |
| Scope of supply | | |
| Delivery quantity in pieces | 1; Built-in keyboard rack mounting | |
| Other | | |
| Merchandise | Yes; TIPRO no. K-647 (K-847) | |
| Manufacturer name | TIPRO Representative Office | |
| Manufacturer's address | Vogelweg 20, 31785 Hameln, Germany | |
| Target devices | Suitable for IPC and HMI devices with the corresponding interfaces (see manual) | |
| Note: | Suitable PS/2 USB adapter (keyboard/mouse): 1x USB 1.1, plug A on 2x PS/2 sockets, 0.20 m, black; manufacturer: Renkforce; supply by Conrad Elektronik, order no.: 1360251 - 62 | |
| Classifications | | |
| | Version | Classification |
| eClass | 14 | 19-20-03-01 |
| eClass | 12 | 19-20-03-01 |
| eClass | 9.1 | 19-20-03-01 |
| eClass | 9 | 19-20-03-01 |
| eClass | 8 | 19-20-03-01 |
| eClass | 7.1 | 19-20-03-01 |
| eClass | 6 | 19-20-03-01 |
| ETIM | 10 | EC001692 |
| ETIM | 9 | EC001692 |
| ETIM | 8 | EC001692 |
| ETIM | 7 | EC001692 |
| IDEA | 4 | 6641 |
| UNSPSC | 15 | 43-21-17-06 |
| Further information | | |

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS

note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

9/29/2021 