

product type designation



**CP 5612**

Communications processor CP 5612 PCI card for connection connection of a PG or PC with PCI bus to PROFIBUS or MPI usable in 32 bit and 64 bit operating systems see also entry ID 22611503.

Technical Product Detail Page

<https://l.siemens.com/1P6GK1561-2AA00>

### transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections

- at the 1st interface / according to PROFIBUS 1

type of electrical connection

- at the 1st interface / according to PROFIBUS 9-pin Sub-D socket (RS 485)
- of the backplane bus PCI (32Bit 3,3V/5V UniversalKey 33/66MHz)

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage

- 1 / from backplane bus 3.3 V
- 2 / from backplane bus 12 V

relative symmetrical tolerance / at DC

- at 3.3 V 9 %
- at 12 V 8 %

consumed current

- 1 / from backplane bus / at DC / maximum 0.15 A
- 2 / from backplane bus / at DC / maximum 0.25 A

power loss [W]

3.5 W

### ambient conditions

ambient temperature

- during operation 5 ... 55 °C
- during storage -20 ... +60 °C
- during transport -20 ... +60 °C

relative humidity / at 25 °C / without condensation / during operation / maximum

95 %

protection class IP

IP00

### design, dimensions and weights

module format

PCI

width

18 mm

height

107 mm

depth

125 mm

net weight

98 g

### product features, product functions, product components / general

number of plug-in cards of same design / plug-in / per PC

1

station	
number of units / note	-
<b>performance data / open communication</b>	
software / for open communication / by means of SEND/RECEIVE / required	Yes, SOFTNET-PB DP / SOFTNET-PB DP Slave / SOFTNET-PB S7
number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50
<b>performance data / PROFIBUS DP</b>	
software / for DP master function / required	Yes, SOFTNET-PB DP
service / as DP master	
• DPV0	Yes
• DPV1	Yes
• DPV2	No
number of DP devices / on DP master / operable	64
data volume	
• of the address range of the inputs / as DP master / total	14640 byte
• of the address range of the outputs / as DP master / total	14640 byte
• of the address range of the inputs / per DP device	244 byte
• of the address range of the outputs / per DP device	244 byte
• of the address range of the diagnostic data / per DP device	244 byte
software / for DP device function / required	Yes, SOFTNET-PB DP slave
service / as DP device	
• DPV0	Yes
• DPV1	No
data volume	
• of the address range of the inputs / as DP device / total	122 byte
• of the address range of the outputs / as DP device / total	122 byte
<b>performance data / S7 communication</b>	
software / for S7 communication / required	Yes, SOFTNET-PB S7
number of possible connections / for S7/PG communication / maximum	8
<b>performance data / multi-protocol mode</b>	
number of configurable connections / per PC station	207
<b>product functions / management, configuration, engineering</b>	
configuration software / required	Included in the scope of delivery of the required software product
<b>product functions / diagnostics</b>	
product function	
• port diagnostics	Yes
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	129.61 kg
• during manufacturing	33.23 kg
• during operation	96.32 kg
• after end of life	0.06 kg
<b>accessories</b>	
accessories	optional: MPI cable
<b>further information / internet links</b>	
internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks.

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](https://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

[Declaration of Conformity](#)



[China RoHS](#)

General Product Approval

EMV

Environment



[KC](#)



last modified:

10/29/2025