

product type designation	<b>IE FC RJ45 Plug 180 (4x2)</b>
product description	RJ45 data connector Industrial Ethernet FastConnect RJ45 plug 180 4x 2, RJ45 plug-in connector (10/100/1000 Mbit/s) with rugged metal enclosure and FC connection system, for IE FC TP cable 4x 2 (AWG24); 180° cable outlet 1 pack = 10 units.



Technical Product Detail Page	<a href="https://l.siemens.com/1P6GK1901-1BB11-2AB0">https://l.siemens.com/1P6GK1901-1BB11-2AB0</a>
suitability for use	For connection to IE FC TP cables 4x2, suitable for fast assembly with the FastConnect system

### transfer rate

transfer rate / for Industrial Ethernet	10, 100, 1000 Mbit/s
---	----------------------

### interfaces

number of electrical connections	
<ul style="list-style-type: none"> <li>for Industrial Ethernet FC TP cables</li> </ul>	1
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>for Industrial Ethernet FC TP cables</li> </ul>	integrated cut-and-clamp contacts for 8-wire TP FC installation cable
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	RJ45 connector
type of electrical connection / FastConnect	Yes

### mechanical data

material / of the enclosure	metal
number of reuses	10
locking mechanism design	other

### design, dimensions and weights

type of cable outlet	180° cable outlet
width	13.7 mm
height	16 mm
depth	55 mm
net weight	35 g
connectable cable cross-section	6.5 ... 8 mm
connectable conductor cross-section	0.21 ... 0.33 mm <sup>2</sup>

### ambient conditions

ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +85 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20

### product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> <li>PoE capability</li> </ul>	Yes

<ul style="list-style-type: none"> <li>PoE+ capability</li> </ul>	Yes
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
product component	
<ul style="list-style-type: none"> <li>strain relief</li> </ul>	Yes

**standards, specifications, approvals**

certificate of suitability	
<ul style="list-style-type: none"> <li>RoHS conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>UL approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>cULus approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>railway application in accordance with EN 50155</li> </ul>	No
standard for structured cabling	Cat6

**further information / internet links**

internet link	
<ul style="list-style-type: none"> <li>to website: Selection guide for cables and connectors</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> </ul>	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to web page: SiePortal</li> </ul>	<a href="https://sieportal.siemens.com">https://sieportal.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx-Download-Manager</li> </ul>	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**security information**

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>
----------------------	---

**Approvals / Certificates**

**General Product Approval**

[Declaration of Conformity](#)



[China RoHS](#)



[Miscellaneous](#)

**Maritime application**      **other**      **Industrial Communication**



[Miscellaneous](#)

[PROFINET](#)

last modified:

10/30/2025