

SCALANCE XRM334; managed layer 2; IE switch, 19" rack; 24x 100/1000 Mbps RJ45 port; 2x 1G/2.5G/5G/10 Gbps RJ45 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,...); CLP included in scope of supply; power supply 24 V DC;



| product type designation | |
|---|---|
| product brand name | SCALANCE |
| product type designation | XRM334 |
| Technical Product Detail Page | https://i.siemens.com/1P6GK5334-2TS01-2AR3 |
| transfer rate | |
| transfer rate | 10, 100, 1000 Mbit/s |
| transfer rate | 2.5, 5, 10 Gbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| • for network components or terminal equipment | 26; RJ45 |
| number of 10/100/1000 Mbit/s RJ45 ports | |
| • with securing collar | 26 |
| number of 1000/2500/5000/10000 Mbps RJ45 ports / with securing collar | 2 |
| number of electrical connections | |
| • for SFP+ | 8; 1000 Mbps and 10000 Mbps SFP usable |
| interfaces / other | |
| number of electrical connections | |
| • for operator console | 1 |
| • for signaling contact | 1 |
| • for power supply | 1 |
| design of the removable storage | |
| • CLP | Yes |
| operating voltage / of the signaling contacts | |
| • at AC / rated value | 24 V |
| • at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| • at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage supply / redundant power supply unit | No |
| type of voltage / 1 / of the supply voltage | |
| • supply voltage / 1 / rated value | 24 V |
| • power loss [W] / 1 / rated value | 72 W |
| • power loss [W] / at DC / at 24 V / typical | 43.2 W |
| • supply voltage / 1 / voltage range | 19.2 ... 31.2 |
| • consumed current / 1 / maximum | 3 A |
| • consumed current / at DC / at 24 V / typical | 1.8 A |
| • product component / 1 / fusing at power supply input | Yes |

| | |
|--|---|
| type of voltage / 2 / of the supply voltage | |
| <ul style="list-style-type: none"> • supply voltage / 2 / rated value • power loss [W] / 2 / rated value • supply voltage / 2 / voltage range • consumed current / 2 / maximum | <p>24 V</p> <p>72 W</p> <p>19.2 ... 30</p> <p>3 A</p> |
| ambient conditions | |
| ambient temperature / in horizontal mounting position / during operation | -40 ... +60 °C; Starting at -40 °C; The maximum ambient temperature during operation depends on the operating height and the plug-in transceivers, see also manual. |
| installation altitude / at height above sea level / maximum | 4000 m |
| relative humidity | |
| <ul style="list-style-type: none"> • at 25 °C / without condensation / during operation / maximum | 95 % |
| operating condition / fanless operation | Yes |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | 19-inch rack |
| number of modular height units / relating to 19-inch cabinet | 1 |
| width | 446 mm |
| height | 43.6 mm |
| depth | 374.8 mm |
| net weight | 8 kg |
| material / of the enclosure | metal |
| fastening method | |
| <ul style="list-style-type: none"> • 19-inch installation | Yes |
| product features, product functions, product components / general | |
| cascading in cases of star topology | any (depending only on signal propagation time) |
| number of automatically learnable MAC addresses | 16382 |
| number of QoS queues / per port | 8 |
| product function | |
| <ul style="list-style-type: none"> • QoS according to IEEE 802.1Q | Yes |
| product feature | |
| <ul style="list-style-type: none"> • Store & Forward switching method | Yes |
| product license | |
| product license / Upgrade license | Yes; layer 3 license |
| product functions / management, configuration, engineering | |
| product function | |
| <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • configuration with STEP 7 • RMON • SMTP server • port mirroring • multiport mirroring • Encapsulated Remote Traffic Mirroring (ERTM) • CoS • PROFINET IO diagnosis • switch-managed | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |
| PROFINET conformity class | B |
| network load class / according to PROFINET | II |
| telegram length / for Ethernet / maximum | 9194 byte |
| protocol / is supported | |
| <ul style="list-style-type: none"> • Telnet • HTTP • HTTPS • TFTP • FTP | <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |

| | |
|---|-----|
| • SFTP | Yes |
| • BOOTP | Yes |
| • NETCONF | Yes |
| • GMRP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| • EtherNet/IP | Yes |
| • SNMP v1 | Yes |
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |
| • IGMP (snooping/querier) | Yes |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function | |
| • port diagnostics | Yes |
| • statistics Packet Size | Yes |
| • statistics packet type | Yes |
| • error statistics | Yes |
| • SysLog | Yes |
| product functions / VLAN | |
| product function | |
| • VLAN - port based | Yes |
| • VLAN - protocol-based | No |
| • VLAN - IP-based | No |
| • VLAN dynamic | Yes |
| number of VLANs / maximum | 512 |
| number of VLANs - dynamic / maximum | 512 |
| product functions / DHCP | |
| product function | |
| • DHCP server | No |
| • DHCP client | Yes |
| • DHCP Option 82 | No |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |
| product functions / redundancy | |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| • media redundancy protocol (MRP) with redundancy manager | Yes |
| • Media Redundancy Protocol Interconnection (MRP-I) | No |
| • ring redundancy | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | No |
| • high speed redundancy protocol (HRP) with standby redundancy | No |
| • redundancy procedure STP | Yes |
| • redundancy procedure RSTP | Yes |
| • redundancy procedure RSTP+ | Yes |
| • redundancy procedure MSTP | Yes |
| • passive listening | No |
| • eRSTP | Yes |
| protocol / is supported | |
| • LACP | No |
| system modification during operation | |
| product function / configuration in RUN via CiR/H-CiR | No |
| product functions / security | |
| product conformity / according to IEEE 802.1x-port based Network Access Control | No |

| | |
|---|--------------|
| protocol / is supported | |
| • RADIUS | Yes |
| • SSH | Yes |
| • SSL | Yes |
| product functions / time | |
| product function | |
| • SICLOCK support | Yes |
| • NTP-client | Yes |
| • IEEE 1588 v2 transparent forwarding | Yes |
| protocol / is supported | |
| • NTP | Yes |
| • SNTP | Yes |
| • IEEE 1588 profile default | Yes |
| accuracy / at IEEE 1588 v2 | |
| • not less than | 100 µs |
| • typical | 50 ns |
| standards, specifications, approvals | |
| certificate of suitability | |
| • CE marking | Yes |
| • UKCA marking | Yes |
| • cULus approval | Yes |
| • KC approval | Yes |
| • Regulatory Compliance Mark (RCM) | Yes |
| product conformity / according to EMC-guideline | 2014/30/EU |
| standard | |
| • for EMC interference emission | EN 61000-6-4 |
| • for immunity to EMC | EN 61000-6-2 |
| standards, specifications, approvals / hazardous environments | |
| certificate of suitability | |
| • ATEX | Yes |
| • UKEX | Yes |
| • IECEX | Yes |
| • ULhazloc approval | Yes |
| • CCC / for hazardous zone according to GB standard | Yes |
| • FM registration | Yes |
| standards, specifications, approvals / other | |
| certificate of suitability | |
| • RoHS conformity | Yes |
| resistance to air pollution / conformity according to ANSI/ISA-71.04 | Yes; G3 |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019 | Yes |
| standards, specifications, approvals / marine classification | |
| Marine classification association | |
| • American Bureau of Shipping Europe Ltd. (ABS) | No |
| • French marine classification society (BV) | No |
| • Chinese Classification Society (CCS) | No |
| • Det Norske Veritas (DNV) | Yes |
| • Korean Register of Shipping (KRS) | No |
| • Lloyds Register of Shipping (LRS) | No |
| • Nippon Kaiji Kyokai (NK) | No |
| • Polski Rejestr Statkow (PRS) | No |
| • Royal Institution of Naval Architects (RINA) | No |
| standards, specifications, approvals / Environmental Product Declaration | |
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| • total | 2101.59 kg |
| • during manufacturing | 132 kg |
| • during operation | 1969 kg |

- after end of life

0.59 kg

product functions / general

| | |
|---|-------------------------------|
| MTBF | 13.2 a |
| reference temperature / for MTBF determination | 40 °C |
| warranty period | 5 a |
| product function / is supported / identification link | Yes; acc. to IEC 61406-1:2022 |

further information / internet links

| | |
|---------------|---|
| internet link | <ul style="list-style-type: none"> • to website: Selection guide for cables and connectors https://support.industry.siemens.com/cs/ww/en/view/109766358 • to web page: selection aid TIA Selection Tool https://www.siemens.com/tstcloud • to website: Industrial communication https://www.siemens.com/simatic-net • to web page: SiePortal https://sieportal.siemens.com/ • to website: Image database https://www.automation.siemens.com/bilddb • to website: CAx-Download-Manager https://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com |
|---------------|---|

security information

| | |
|----------------------|---|
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p> |
|----------------------|---|

Approvals / Certificates

General Product Approval



[China RoHS](#)



[TUEV](#)

| | | |
|--------------------------------|---|-------------------|
| For use in hazardous locations | Radio Equipment Type Approval Certificate | Test Certificates |
|--------------------------------|---|-------------------|



[FM](#)

[CCC-Ex](#)

[KC](#)

[Type Test Certificates/Test Report](#)

Maritime application Environment Industrial Communication



[PROFINET](#)

last modified:

10/30/2025