

SCALANCE XRM334; managed layer 2, IE switch, 19" rack; 2x 1G/2.5G/5G/10 Gbps RJ45 port, 24x 100M/1G SFP port; 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,...); CLP included in scope of supply; power supply 24 V DC;



product type designation	
product brand name	SCALANCE
product type designation	XRM334
Technical Product Detail Page	https://i.siemens.com/1P6GK5334-5TS01-2AR3
transfer rate	
transfer rate	100, 1000 Mbit/s
transfer rate	2.5, 5, 10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
• for network components or terminal equipment	2; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
• with securing collar	0
number of 1000/2500/5000/10000 Mbps RJ45 ports / with securing collar	2
number of electrical connections	
• for SFP	24; 100 Mbps and 1000 Mbps SFP usable
• for SFP+	8; 1000 Mbps and 10000 Mbps SFP usable
interfaces / other	
number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	2
design of the removable storage	
• CLP	Yes
operating voltage / of the signaling contacts	
• at AC / rated value	24 V
• at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	
• supply voltage / 1 / rated value	24 V
• power loss [W] / 1 / rated value	72 W
• power loss [W] / at DC / at 24 V / typical	43.2 W
• supply voltage / 1 / voltage range	19.2 ... 31.2
• consumed current / 1 / maximum	3 A
• consumed current / at DC / at 24 V / typical	1.8 A

<ul style="list-style-type: none"> product component / 1 / fusing at power supply input 	Yes
type of voltage / 2 / of the supply voltage	
<ul style="list-style-type: none"> supply voltage / 2 / rated value 	24 V
<ul style="list-style-type: none"> power loss [W] / 2 / rated value 	76.8 W
<ul style="list-style-type: none"> supply voltage / 2 / voltage range 	19.2 ... 30
<ul style="list-style-type: none"> consumed current / 2 / maximum 	3.2 A
ambient conditions	
ambient temperature / in horizontal mounting position / during operation	-40 ... +55 °C; Starting at -40 °C; The maximum ambient temperature during operation depends on the operating height and the plug-in transceivers, see also manual.
installation altitude / at height above sea level / maximum	4000 m
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
operating condition / fanless operation	Yes
protection class IP	IP20
design, dimensions and weights	
design	19-inch rack
number of modular height units / relating to 19-inch cabinet	1
width	446 mm
height	43.6 mm
depth	374.8 mm
net weight	8 kg
material / of the enclosure	metal
fastening method	
<ul style="list-style-type: none"> 19-inch installation 	Yes
product features, product functions, product components / general	
cascading in the case of a redundant ring / at reconfiguration time of ≤ 0.3-s	50
cascading in cases of star topology	any (depending only on signal propagation time)
number of automatically learnable MAC addresses	16382
number of QoS queues / per port	8
product function	
<ul style="list-style-type: none"> QoS according to IEEE 802.1Q 	Yes
product feature	
<ul style="list-style-type: none"> Store & Forward switching method 	Yes
product license	
product license / Upgrade license	Yes; layer 3 license
product functions / management, configuration, engineering	
product function	
<ul style="list-style-type: none"> CLI 	Yes
<ul style="list-style-type: none"> web-based management 	Yes
<ul style="list-style-type: none"> MIB support 	Yes
<ul style="list-style-type: none"> TRAPs via email 	Yes
<ul style="list-style-type: none"> configuration with STEP 7 	Yes
<ul style="list-style-type: none"> RMON 	Yes
<ul style="list-style-type: none"> SMTP server 	No
<ul style="list-style-type: none"> port mirroring 	Yes
<ul style="list-style-type: none"> multiport mirroring 	Yes
<ul style="list-style-type: none"> Encapsulated Remote Traffic Mirroring (ERTM) 	Yes
<ul style="list-style-type: none"> CoS 	Yes
<ul style="list-style-type: none"> PROFINET IO diagnosis 	Yes
<ul style="list-style-type: none"> switch-managed 	Yes
PROFINET conformity class	B
network load class / according to PROFINET	III
telegram length / for Ethernet / maximum	9194 byte
protocol / is supported	
<ul style="list-style-type: none"> Telnet 	Yes
<ul style="list-style-type: none"> HTTP 	Yes
<ul style="list-style-type: none"> HTTPS 	Yes

• TFTP	Yes
• FTP	Yes
• SFTP	Yes
• BOOTP	Yes
• NETCONF	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
• port diagnostics	Yes
• statistics Packet Size	Yes
• statistics packet type	Yes
• error statistics	Yes
• SysLog	Yes
product functions / VLAN	
product function	
• VLAN - port based	Yes
• VLAN - protocol-based	No
• VLAN - IP-based	No
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	257
product functions / DHCP	
product function	
• DHCP server	Yes
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Media Redundancy Protocol Interconnection (MRP-I)	No
• ring redundancy	Yes
• high speed redundancy protocol (HRP) with redundancy manager	No
• high speed redundancy protocol (HRP) with standby redundancy	No
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure RSTP+	Yes
• redundancy procedure MSTP	Yes
• passive listening	No
protocol / is supported	
• LACP	No
system modification during operation	
product function / configuration in RUN via CiR/H-CiR	No
product functions / security	

product function	
• IEEE 802.1x (radius)	Yes
• broadcast/multicast/unicast limiter	Yes
• broadcast blocking	Yes
protocol / is supported	
• SSH	Yes
• SSL	Yes
product functions / time	
product function	
• SICLOCK support	Yes
• NTP-client	Yes
• SNTP client	Yes
• IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
• NTP	Yes
• SNTP	Yes
• IEEE 1588 profile default	No
accuracy / at IEEE 1588 v2	
• not less than	100 µs
• typical	50 ns
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
• UKCA marking	Yes
• cULus approval	Yes
• KC approval	Yes
• Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
• for EMC interference emission	EN 61000-6-4
• for immunity to EMC	EN 61000-6-2
• for safety / from CSA and UL	UL 62368-1, UL 61010
standards, specifications, approvals / hazardous environments	
certificate of suitability	
• ATEX	Yes
• UKEX	Yes
• IECEx	Yes
• ULhazloc approval	Yes
• CCC / for hazardous zone according to GB standard	Yes
• FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
• RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	2239.67 kg
• during manufacturing	138 kg
• during operation	2101 kg
• after end of life	0.67 kg
product functions / general	
MTBF	16.7 a
reference temperature / for MTBF determination	40 °C
warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022

further information / internet links

internet link

- to website: Selection guide for cables and connectors
- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to web page: SiePortal
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support




- <https://support.industry.siemens.com/cs/ww/en/view/109766358>
- <https://www.siemens.com/tstcloud>
- <https://www.siemens.com/simatic-net>
- <https://sieportal.siemens.com/>
- <https://www.automation.siemens.com/bilddb>
- <https://www.siemens.com/cax>
- <https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval	Test Certificates	Environment
 	China RoHS Type Test Certificates/Test Report	

last modified:

11/7/2025 