



SCALANCE XC416-8 managed Layer 3 IE switch, 16x 10/100/1000 Mbps RJ45, 8x 1G/10 Gbps SFP+ port, LED diagnostics, error signaling contact with select/set button; PROFINET IO; device; network management, redundancy functions; office features (RSTP, VLAN, IGMP,...); CLP included in scope of supply; assembly: DIN rail/S7 mounting rail

| product type designation | |
|---|---|
| product brand name | SCALANCE |
| product type designation | XC416-8 |
| Technical Product Detail Page | https://l.siemens.com/1P6GK5424-8TR00-2AC2 |
| transfer rate | |
| transfer rate | 10, 100, 1000 Mbit/s |
| transfer rate | 10 Gbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| • for network components or terminal equipment | 16; RJ45 with securing collar |
| number of 10/100/1000 Mbit/s RJ45 ports | |
| • with securing collar | 16 |
| number of electrical connections | |
| • for SFP+ | 8; 1000 Mbps and 10000 Mbps SFP usable |
| interfaces / other | |
| number of electrical connections | |
| • for operator console | 1 |
| • for signaling contact | 1 |
| • for power supply | 2 |
| design of the removable storage | |
| • CLP | Yes |
| operating voltage / of the signaling contacts | |
| • at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| • at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| product component / connection for redundant voltage supply | Yes |
| type of voltage supply / redundant power supply unit | No |
| type of voltage / 1 / of the supply voltage | |
| • supply voltage / 1 / rated value | 24 V |
| • power loss [W] / 1 / rated value | 43.2 W |
| • power loss [W] / at DC / at 24 V / typical | 25.92 W |
| • supply voltage / 1 / voltage range | 19.2 ... 28.8 |
| • consumed current / 1 / maximum | 1.8 A |
| • consumed current / at DC / at 24 V / typical | 1.08 A |
| • product component / 1 / fusing at power supply input | Yes |
| ambient conditions | |
| ambient temperature | |
| • during operation | -40 ... +60 °C |

| | |
|--|----------------|
| <ul style="list-style-type: none"> during storage | -40 ... +85 °C |
| <ul style="list-style-type: none"> during transport | -40 ... +85 °C |
| relative humidity | |
| <ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum | 95 % |
| operating condition / fanless operation | Yes |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | compact |
| width | 210 mm |
| height | 147 mm |
| depth | 125 mm |
| net weight | 1.8 kg |
| fastening method | |
| <ul style="list-style-type: none"> 19-inch installation | No |
| <ul style="list-style-type: none"> 35 mm DIN-rail mounting | Yes |
| <ul style="list-style-type: none"> wall mounting | Yes |
| <ul style="list-style-type: none"> S7-300 rail mounting | Yes |
| <ul style="list-style-type: none"> S7-1500 rail mounting | Yes |
| product features, product functions, product components / general | |
| cascading in the case of a redundant ring / at reconfiguration time of $\leq 0.3\text{s}$ | 50 |
| number of automatically learnable MAC addresses | 16382 |
| number of QoS queues / per port | 8 |
| product function | |
| <ul style="list-style-type: none"> QoS according to IEEE 802.1Q | Yes |
| product feature | |
| <ul style="list-style-type: none"> Store & Forward switching method | Yes |
| product functions / management, configuration, engineering | |
| product function | |
| <ul style="list-style-type: none"> CLI | Yes |
| <ul style="list-style-type: none"> web-based management | Yes |
| <ul style="list-style-type: none"> MIB support | Yes |
| <ul style="list-style-type: none"> TRAPs via email | Yes |
| <ul style="list-style-type: none"> configuration with STEP 7 | Yes |
| <ul style="list-style-type: none"> RMON | Yes |
| <ul style="list-style-type: none"> port mirroring | Yes |
| <ul style="list-style-type: none"> multiport mirroring | Yes |
| <ul style="list-style-type: none"> CoS | Yes |
| <ul style="list-style-type: none"> PROFINET IO diagnosis | Yes |
| <ul style="list-style-type: none"> switch-managed | Yes |
| PROFINET conformity class | B |
| network load class / according to PROFINET | III |
| telegram length / for Ethernet / maximum | 9194 byte |
| protocol / is supported | |
| <ul style="list-style-type: none"> Telnet | Yes |
| <ul style="list-style-type: none"> HTTP | Yes |
| <ul style="list-style-type: none"> HTTPS | Yes |
| <ul style="list-style-type: none"> TFTP | Yes |
| <ul style="list-style-type: none"> FTP | Yes |
| <ul style="list-style-type: none"> SFTP | Yes |
| <ul style="list-style-type: none"> BOOTP | Yes |
| <ul style="list-style-type: none"> NETCONF | No |
| <ul style="list-style-type: none"> GMRP | Yes |
| <ul style="list-style-type: none"> DCP | Yes |
| <ul style="list-style-type: none"> LLDP | Yes |
| <ul style="list-style-type: none"> EtherNet/IP | Yes |
| <ul style="list-style-type: none"> SNMP v1 | Yes |
| <ul style="list-style-type: none"> SNMP v2 | Yes |

| | |
|---|-----------------------|
| • SNMP v3 | Yes |
| • IGMP (snooping/querier) | Yes |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function | |
| • port diagnostics | Yes |
| • statistics Packet Size | Yes |
| • statistics packet type | Yes |
| • error statistics | Yes |
| • SysLog | Yes |
| product functions / VLAN | |
| product function | |
| • VLAN - port based | Yes |
| • VLAN - protocol-based | No |
| • VLAN - IP-based | No |
| • VLAN dynamic | Yes |
| number of VLANs / maximum | 257 |
| number of VLANs - dynamic / maximum | 257 |
| number of VLANs / at ring redundancy (HRP; MRP; standby link) | 257 |
| product functions / DHCP | |
| product function | |
| • DHCP server | Yes |
| • DHCP client | Yes |
| • DHCP Option 82 | Yes |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |
| product functions / routing | |
| service / routing / note | IP routing integrated |
| product function | |
| • static IP routing | Yes |
| • static IP routing IPv6 | No |
| • dynamic IP routing | Yes |
| • dynamic IP routing IPv6 | No |
| protocol / is supported | |
| • RIPv2 | Yes |
| • RIPnG for IPv6 | No |
| • OSPFv2 | Yes |
| • OSPFv3 for IPv6 | No |
| • VRRP | Yes |
| • VRRP for IPv6 | No |
| product functions / redundancy | |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| • media redundancy protocol (MRP) with redundancy manager | Yes |
| • Media Redundancy Protocol Interconnection (MRP-I) | Yes |
| • of the PROFINET IO device / is supported / PROFINET system redundancy | Yes |
| • ring redundancy | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes |
| • high speed redundancy protocol (HRP) with standby redundancy | Yes |
| • redundancy procedure STP | Yes |
| • redundancy procedure RSTP | Yes |
| • redundancy procedure RSTP+ | Yes |
| • redundancy procedure MSTP | Yes |

| | |
|---|--|
| <ul style="list-style-type: none"> • High-availability Seamless Redundancy (HSR) | Yes |
| <ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/operation in the PRP-network | Yes |
| <ul style="list-style-type: none"> • Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | Yes |
| <ul style="list-style-type: none"> • passive listening | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • LACP | Yes |
| system modification during operation | |
| product function / configuration in RUN via CiR/H-CiR | Yes |
| product functions / security | |
| product function | |
| <ul style="list-style-type: none"> • IEEE 802.1x (radius) | Yes |
| <ul style="list-style-type: none"> • broadcast/multicast/unicast limiter | Yes |
| <ul style="list-style-type: none"> • broadcast blocking | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • SSH | Yes |
| <ul style="list-style-type: none"> • SSL | Yes |
| product functions / time | |
| product function | |
| <ul style="list-style-type: none"> • SICLOCK support | Yes |
| <ul style="list-style-type: none"> • NTP-client | Yes |
| <ul style="list-style-type: none"> • SNTP client | Yes |
| <ul style="list-style-type: none"> • IEEE 1588 v2 transparent forwarding | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • NTP | Yes |
| <ul style="list-style-type: none"> • SNTP | Yes |
| accuracy / at IEEE 1588 v2 | |
| <ul style="list-style-type: none"> • not less than | 100 µs |
| <ul style="list-style-type: none"> • typical | 50 ns |
| standards, specifications, approvals | |
| certificate of suitability | |
| <ul style="list-style-type: none"> • CE marking | Yes |
| <ul style="list-style-type: none"> • UKCA marking | Yes |
| <ul style="list-style-type: none"> • cULus approval | Yes |
| <ul style="list-style-type: none"> • KC approval | Yes |
| <ul style="list-style-type: none"> • Regulatory Compliance Mark (RCM) | Yes |
| standard | |
| <ul style="list-style-type: none"> • for EMC interference emission | EN 61000-6-4 (Class A) |
| <ul style="list-style-type: none"> • for immunity to EMC | EN 61000-6-2 |
| <ul style="list-style-type: none"> • for safety / from CSA and UL | UL 60950-1; CSA C22.2 No. 213-M1987 |
| standards, specifications, approvals / hazardous environments | |
| certificate of suitability | |
| <ul style="list-style-type: none"> • CCC / for hazardous zone according to GB standard | Yes |
| standards, specifications, approvals / other | |
| certificate of suitability | |
| <ul style="list-style-type: none"> • railway application in accordance with EN 50125-3 | Yes; Section 4.2: Class AX (up to 2000m); section 4.3: T1: Containers N.T.C and T.C. / Buildings N.C.C and C.C, T2: Containers N.T.C and T.C. / Buildings N.C.C and C.C, TX: Containers N.T.C and T.C. / Buildings N.C.C and C.C., derating according to the manual must be observed when SFP/SFP+ transceivers are used --> only for variants with optical connections; In addition, depending on the installation position, the derating according to the manual must be taken into account; section 4.4: T1: Containers C.C. / Buildings N.C.C and C.C., T2: Containers C.C. / Buildings N.C.C and C.C, T3: Containers C.C. / Buildings N.C.C and C.C; section 4.11: C1: Indoor, C2: Indoor (except condensation), C3: Indoor (except condensation), 4B1, 4S10, UL 61010-2-10; section 4.13: partially, Test Fc: Vibration EN 60068-2-6; IEC 60068-2-6, Test Ea: Shock EN 60068-2-27; IEC 60068-2-27, Test Ec: Rough handling, shocks EN 60068-2-31; IEC 60068-2-31; section 4.14: yes; section 4.15: yes, according to manual. |
| resistance to air pollution / conformity according to ANSI/ISA-71.04 | Yes; G3 |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019 | Yes |

standards, specifications, approvals / Environmental Product Declaration

| | |
|--|--|
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| <ul style="list-style-type: none"> • total • during manufacturing • during operation • after end of life | <p>1244.3 kg</p> <p>122.74 kg</p> <p>1120.64 kg</p> <p>0.91 kg</p> |

product functions / general

| | |
|---|-------------------------------|
| warranty period | 5 a |
| product function / is supported / identification link | Yes; acc. to IEC 61406-1:2022 |

further information / internet links

| | |
|---|--|
| internet link | |
| <ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to web page: SiePortal • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support | <p>https://support.industry.siemens.com/cs/ww/en/view/109766358</p> <p>https://www.siemens.com/tstcloud</p> <p>https://www.siemens.com/simatic-net</p> <p>https://sieportal.siemens.com/</p> <p>https://www.automation.siemens.com/bilddb</p> <p>https://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p> |

security information

| | |
|----------------------|---|
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p> |
|----------------------|---|

Approvals / Certificates

General Product Approval



[China RoHS](#)



[TUEV](#)

For use in hazardous locations Test Certificates Environment



[FM](#)

[CCC-Ex](#)

[Type Test Certificates/Test Report](#)



Industrial Communication

[PROFINET](#)

last modified:

10/30/2025