

SCALANCE XR528-6M; managed IE switch; 19" rack; 4x 1000/10000 Mbit/s SFP+; 6x 100/1000 Mbit/s 4-port media modules, electrical, electrical PoE or optical; LED diagnostics; error signaling contact; Select/set pushbutton, PROFINET IO device, network management, integrated redundancy manager; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery Layer 3 integrated; ports in the front.



| product type designation | |
|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| product brand name | SCALANCE |
| product type designation | XR528-6M |
| Technical Product Detail Page | https://i.siemens.com/1P6GK5528-0AR00-2AR2 |
| transfer rate | |
| transfer rate | 10, 100, 1000 Mbit/s |
| transfer rate | 10 Gbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| <ul style="list-style-type: none"> for network components or terminal equipment | RJ45 |
| <ul style="list-style-type: none"> for Power-over-Ethernet / for network components or terminal equipment | 12 |
| number of electrical connections | |
| <ul style="list-style-type: none"> for SFP+ | 4 |
| interfaces / for communication / plug-in | |
| number of 100 Mbit/s ST(BFOC) ports | |
| <ul style="list-style-type: none"> for multimode | 24 |
| <ul style="list-style-type: none"> for single mode (LD) | 24 |
| number of 1000 Mbit/s SC ports | |
| <ul style="list-style-type: none"> for multimode | 24 |
| <ul style="list-style-type: none"> for single mode (LD) | 24 |
| number of electrical connections | |
| <ul style="list-style-type: none"> for SFP | 4 |
| <ul style="list-style-type: none"> for SFP+ | 4 |
| interfaces / other | |
| number of electrical connections | |
| <ul style="list-style-type: none"> for operator console | 1 |
| <ul style="list-style-type: none"> for signaling contact | 1 |
| <ul style="list-style-type: none"> for media module | 6 |
| <ul style="list-style-type: none"> for power supply | 1 |
| product feature / hot-swappable interface modules | Yes |
| operating voltage / of the signaling contacts | |
| <ul style="list-style-type: none"> at DC / rated value | 24 V |
| operational current / of the signaling contacts | |
| <ul style="list-style-type: none"> at DC / maximum | 0.1 A |
| supply voltage, current consumption, power loss | |
| type of voltage supply / redundant power supply unit | No |
| supplied active power / of PSE / with PoE | |
| <ul style="list-style-type: none"> per port / maximum | 30 W |

| | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> total / maximum | 180 W |
| type of voltage / 1 / of the supply voltage | |
| <ul style="list-style-type: none"> supply voltage / 1 / rated value power loss [W] / 1 / rated value supply voltage / 1 / voltage range consumed current / 1 / maximum product component / 1 / fusing at power supply input | 24 V 22 W 19.2 ... 28.8 11.5 A Yes |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation during storage during transport note | 0 ... 60 °C -40 ... +70 °C -40 ... +70 °C Operation with integral fan, replaceable |
| relative humidity | |
| <ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | 19-inch rack |
| number of modular height units / relating to 19-inch cabinet | 2 |
| width | 449 mm |
| height | 87.2 mm |
| depth | 305 mm |
| net weight | 7.2 kg |
| fastening method | |
| <ul style="list-style-type: none"> 19-inch installation 35 mm DIN-rail mounting wall mounting S7-300 rail mounting S7-1500 rail mounting | Yes No No No No |
| type of cable outlet | Cable outlet at front |
| product features, product functions, product components / general | |
| cascading in cases of star topology | any (depending only on signal propagation time) |
| product functions / management, configuration, engineering | |
| product function | |
| <ul style="list-style-type: none"> CLI web-based management MIB support TRAPs via email configuration with STEP 7 RMON port mirroring multiport mirroring CoS PROFINET IO diagnosis switch-managed | Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes |
| PROFINET conformity class | B |
| telegram length / for Ethernet / maximum | 9216 byte |
| protocol / is supported | |
| <ul style="list-style-type: none"> Telnet HTTP HTTPS TFTP FTP BOOTP GMRP DCP LLDP SNMP v1 | Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes |

| | |
|----------------------------------------------------------------|-----------------------|
| • SNMP v2 | Yes |
| • SNMP v3 | Yes |
| • IGMP (snooping/querier) | Yes |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function | |
| • port diagnostics | Yes |
| • statistics Packet Size | Yes |
| • statistics packet type | Yes |
| • error statistics | Yes |
| • SysLog | Yes |
| product functions / VLAN | |
| product function | |
| • VLAN - port based | Yes |
| • VLAN - protocol-based | Yes |
| • VLAN - IP-based | Yes |
| • VLAN dynamic | Yes |
| number of VLANs / maximum | 255 |
| number of VLANs - dynamic / maximum | 255 |
| product functions / DHCP | |
| product function | |
| • DHCP client | Yes |
| • DHCP Option 82 | Yes |
| • DHCP Option 66 | Yes |
| • DHCP Option 67 | Yes |
| product functions / routing | |
| service / routing / note | IP routing integrated |
| product function | |
| • static IP routing | Yes |
| • static IP routing IPv6 | Yes |
| • dynamic IP routing | Yes |
| • dynamic IP routing IPv6 | Yes |
| protocol / is supported | |
| • RIPv2 | Yes |
| • RIPnG for IPv6 | Yes |
| • OSPFv2 | Yes |
| • OSPFv3 for IPv6 | Yes |
| • VRRP | Yes |
| • VRRP for IPv6 | Yes |
| product functions / redundancy | |
| protocol / is supported / Media Redundancy Protocol (MRP) | Yes |
| product function | |
| • media redundancy protocol (MRP) with redundancy manager | Yes |
| • Media Redundancy Protocol Interconnection (MRP-I) | Yes |
| • ring redundancy | Yes |
| • high speed redundancy protocol (HRP) with redundancy manager | Yes |
| • high speed redundancy protocol (HRP) with standby redundancy | Yes |
| • redundancy procedure STP | Yes |
| • redundancy procedure RSTP | Yes |
| • redundancy procedure RSTP+ | Yes |
| • redundancy procedure MSTP | Yes |
| • passive listening | Yes |
| protocol / is supported | |
| • LACP | Yes |

product functions / security

| | |
|---------------------------------------|-----|
| product function | |
| • IEEE 802.1x (radius) | Yes |
| • broadcast/multicast/unicast limiter | Yes |
| • broadcast blocking | Yes |
| protocol / is supported | |
| • SSH | Yes |

product functions / time

| | |
|------------------------------|-----------|
| product function | |
| • SICLOCK support | Yes |
| protocol / is supported | |
| • NTP | Yes |
| • SNTP | Yes |
| type of time synchronization | IEEE 1588 |

standards, specifications, approvals

| | |
|------------------------------------|--------------------------------------|
| certificate of suitability | |
| • CE marking | Yes |
| • KC approval | Yes |
| • Regulatory Compliance Mark (RCM) | Yes |
| standard | |
| • for EMC interference emission | EN 61000-6-4 (Class A) |
| • for immunity to EMC | EN 61000-6-2 |
| • for safety / from CSA and UL | UL 60950-1, CSA C22.2 No. 60950-1-03 |

standards, specifications, approvals / hazardous environments

| | |
|-----------------------------------------------------|-----|
| certificate of suitability | |
| • ATEX | Yes |
| • UKEX | Yes |
| • IECEx | Yes |
| • ULhazloc approval | Yes |
| • CCC / for hazardous zone according to GB standard | Yes |
| • FM registration | Yes |

standards, specifications, approvals / other

| | |
|---------------------------------------------------------------------------------|---------|
| certificate of suitability | |
| • RoHS conformity | Yes |
| resistance to air pollution / conformity according to ANSI/ISA-71.04 | Yes; G3 |
| IT security for industrial automation systems / according to IEC 62443-4-2:2019 | Yes |

standards, specifications, approvals / Environmental Product Declaration

| | |
|-----------------------------------|-----------|
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] | |
| • total | 742.98 kg |
| • during manufacturing | 132 kg |
| • during operation | 610.39 kg |
| • after end of life | 0.59 kg |

product functions / general

| | |
|-----------------|-----|
| warranty period | 5 a |
|-----------------|-----|

further information / internet links

| | |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| internet link | |
| • to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to website: Industrial communication | https://www.siemens.com/simatic-net |
| • to web page: SiePortal | https://sieportal.siemens.com/ |
| • to website: Image database | https://www.automation.siemens.com/bilddb |
| • to website: CAx-Download-Manager | https://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

security information

| | |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



[China RoHS](#)



EMV

For use in hazardous locations

Maritime application

[KC](#)



[FM](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Environment

Industrial Communication



[PROFINET](#)

last modified:

10/30/2025