

### product type designation



### W722-1 RJ45 (ISR)

IWLAN client, SCALANCE W722-1, RJ45, 1 radio, 1 R-SMA antenna port, iFeatures support IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; only for operation in Israel.

Technical Product Detail Page

<https://l.siemens.com/1P6GK5722-1FC00-0AC0>

### transfer rate

#### transfer rate

- |                           |                |
|---------------------------|----------------|
| • with WLAN / maximum     | 150 Mbit/s     |
| • for Industrial Ethernet | 10, 100 Mbit/s |

### interfaces

#### number of electrical connections

- |  |   |
|--|---|
| • for network components or terminal equipment | 1 |
| • for power supply                             | 1 |
| • for redundant voltage supply                 | 0 |

#### type of electrical connection

- |  |                       |
|--|-----------------------|
| • for network components or terminal equipment | RJ45 socket           |
| • for power supply                             | 3-pole screw terminal |

### memory

#### design of the removable storage

- |            |    |
|------------|----|
| • C-PLUG   | No |
| • KEY-PLUG | No |

### interfaces / wireless

#### number of radio cards / permanently installed

1

#### number of electrical connections / for external antenna(s)

1

#### type of electrical connection / for external antenna(s)

R-SMA (socket)

#### product feature / external antenna can be mounted directly on device

Yes

### supply voltage, current consumption, power loss

#### type of voltage / of the supply voltage

DC

#### consumed current

- |                             |        |
|-----------------------------|--------|
| • at DC / at 24 V / typical | 0.15 A |
|-----------------------------|--------|

#### power loss [W]

- |                             |       |
|-----------------------------|-------|
| • at DC / at 24 V / typical | 3.6 W |
|-----------------------------|-------|

#### supply voltage / 1

- |                       |        |
|-----------------------|--------|
| • from terminal block | 19.2 V |
|-----------------------|--------|

#### supply voltage / 2

- |                       |        |
|-----------------------|--------|
| • from terminal block | 28.8 V |
|-----------------------|--------|

### ambient conditions

#### ambient temperature

- |                    |                |
|--------------------|----------------|
| • during operation | 0 ... 55 °C    |
| • during storage   | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |

relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20

**design, dimensions and weights**

width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
• 35 mm DIN-rail mounting	Yes
• wall mounting	No

**radio frequencies**

operating frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz; depending on the country approvals
• for WLAN in 5 GHz frequency band	5.15 ... 5.35 GHz; depending on the country approvals

**product features, product functions, product components / general**

product function / Access Point Mode	No
product function / client Mode	Yes
product function	
• iPCF client	Yes
• iPCF-MC client	Yes
number of iPCF-capable radio modules	1
product function / iPRP	Yes

**product functions / management, configuration, engineering**

number of manageable IP addresses / in client	4
product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• WDS	No
protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	No
identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 - higher level designation/location designation	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022

**product functions / diagnostics**

product function	
• PROFINET IO diagnosis	Yes
• link check	No
• connection monitoring IP-Alive	No

<ul style="list-style-type: none"> <li>• SysLog</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
<b>product functions / VLAN</b>	
product function	
<ul style="list-style-type: none"> <li>• function VLAN with IWLAN</li> </ul>	No
<b>product functions / DHCP</b>	
product function	
<ul style="list-style-type: none"> <li>• DHCP client</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP server</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• DHCP Option 82</li> </ul>	Yes
<b>product functions / redundancy</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• STP/RSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MSTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RSTP</li> </ul>	Yes
<b>product functions / security</b>	
product function	
<ul style="list-style-type: none"> <li>• ACL - MAC-based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• management security, ACL-IP based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.1x (radius)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• NAT/NAPT</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• access protection according to IEEE802.11i</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• WPA/WPA2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TKIP/AES</li> </ul>	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>• SSH</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RADIUS</li> </ul>	Yes
<b>product functions / time</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>• NTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SIMATIC time synchronization (SIMATIC Time)</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1 E115352, CSA C22.2 No. 60950-1
certificate of suitability	
<ul style="list-style-type: none"> <li>• EC Declaration of Conformity</li> </ul>	No
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	No
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• E1 approval</li> </ul>	No
<ul style="list-style-type: none"> <li>• railway application in accordance with EN 50155</li> </ul>	No
<ul style="list-style-type: none"> <li>• NEMA TS2</li> </ul>	No
<ul style="list-style-type: none"> <li>• IEC 61375</li> </ul>	No
<ul style="list-style-type: none"> <li>• IEC 61850-3</li> </ul>	No
<ul style="list-style-type: none"> <li>• NEMA4X</li> </ul>	No
<ul style="list-style-type: none"> <li>• Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af</li> </ul>	No
<ul style="list-style-type: none"> <li>• Power-over-Ethernet according to IEEE802.3at for type 2</li> </ul>	No
standard for wireless communication	
<ul style="list-style-type: none"> <li>• IEEE 802.11a</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11b</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11e</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11g</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IEEE 802.11h</li> </ul>	Yes

<ul style="list-style-type: none"> <li>• IEEE 802.11i</li> <li>• IEEE 802.11n</li> </ul>	<p>Yes</p> <p>Yes</p>
wireless approval	You will find the current list of countries at: <a href="http://www.siemens.de/funkzulassungen">www.siemens.de/funkzulassungen</a>
<b>standards, specifications, approvals / marine classification</b>	
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• French marine classification society (BV)</li> <li>• DNV GL</li> <li>• Korean Register of Shipping (KRS)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> <li>• Royal Institution of Naval Architects (RINA)</li> </ul>	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
<b>standards, specifications, approvals / hazardous environments</b>	
standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> <li>• from CSA and UL</li> </ul>	ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> <li>• total</li> <li>• during manufacturing</li> <li>• during operation</li> <li>• after end of life</li> </ul>	<p>200.91 kg</p> <p>12.97 kg</p> <p>187.77 kg</p> <p>0.17 kg</p>
<b>accessories</b>	
accessories	24 V DC screw terminal included in scope of delivery
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> <li>• to web page: selection aid TIA Selection Tool</li> <li>• to web page: WLAN country approval</li> <li>• to the website: IWLAN</li> <li>• to website: Industrial communication</li> <li>• to web page: SiePortal</li> <li>• to website: Image database</li> <li>• to website: CAX-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<p><a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a></p> <p><a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a></p> <p><a href="https://www.siemens.com/wireless-approvals">https://www.siemens.com/wireless-approvals</a></p> <p><a href="https://www.siemens.com/iwlan">https://www.siemens.com/iwlan</a></p> <p><a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a></p> <p><a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a></p> <p><a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a></p> <p><a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)
<b>Approvals / Certificates</b>	
General Product Approval	For use in hazardous locations



[Declaration of Con-  
formity](#)



[Manufacturer Declara-  
tion](#)

[China RoHS](#)

[CCC-Ex](#)

Radio Equipment  
Type Approval Certi-  
ficate

Environment

[Miscellaneous](#)



last modified:

10/29/2025