

product type designation

RUGGEDCOM SFP1132-1LX115

RUGGEDCOM Accessory, SFP, 1 X 1000MBIT/S, 1000BASE-LX, LC-Interface, Optical: Single Mode Fiber Optic up to max. 115km, 1550nm, -10...+70 Degrees Celsius



Figure similar

Technical Product Detail Page

<https://l.siemens.com/1P6GK6000-8FE56-0AA0>

suitability for operation

compatible to RUGGEDCOM products with SFP-Slot

interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of optical interfaces / for network components or terminal equipment / maximum	1
number of 1000 Mbit/s LC ports / for multimode / integrated	1
design of the optical interface / for network components or terminal equipment	LC
range / at the optical interface / depending on the optical fiber used	115 km

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	<p>-10 ... +70 °C</p> <p>-40 ... +80 °C</p> <p>-40 ... +80 °C</p>
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %

design, dimensions and weights

design	SFP Module
width	14 mm
height	9 mm
depth	57 mm
net weight	0.01 kg
product feature / conformal coating	No
fastening method	latched

standards, specifications, approvals

standard	
<ul style="list-style-type: none"> for safety / from CSA and UL for emitted interference for interference immunity 	<p>UL 60950-1, CSA C22.2 No. 60950-7</p> <p>EN 61000-6-4 (Class A)</p> <p>EN 61000-6-2</p>
laser protection class	21 CFR Chapter 1, Subchapter J
certificate of suitability	EN 61000-6-2, EN 61000-6-10
<ul style="list-style-type: none"> CE marking C-Tick KC approval E1 approval 	<p>Yes</p> <p>No</p> <p>No</p> <p>No</p>

- IEC 61850-3

Yes

further information / internet links

internet link

- to website: Selection guide for cables and connectors
- to website: Industry Mall/RUGGEDCOM selector
- to website: Industrial communication
- to website: Siemens RUGGEDCOM
- to web page: SiePortal
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/109766358>
<https://www.siemens.com/ruggedcom-selector>
<https://www.siemens.com/simatic-net>
<https://www.siemens.com/ruggedcom>
<https://sieportal.siemens.com/>
<https://www.automation.siemens.com/bilddb>
<https://www.siemens.com/cax>
<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

other

[Manufacturer Declaration](#)



[inspection certificate](#)

last modified:

11/14/2025