

product type designation

**RUGGEDCOM 2488-24FXA01 Module CC**

Media Module for RUGGEDCOM RSG 2488, 4 x 100Mbit/s ST-interface, Optical: 100BASE-FX, Multi Mode fiber optic up to 2 kilo meter, 1300nm with Conformal Coating



Figure similar

Technical Product Detail Page

<https://l.siemens.com/1P6GK6000-8FX01-4EA1>

suitability for operation

RSG2488

### interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of optical interfaces / for network components or terminal equipment / maximum	4
number of 100 Mbit/s ST(BFOC) ports / for multimode / integrated	4
design of the optical interface / for network components or terminal equipment	ST
range / at the optical interface / depending on the optical fiber used	2 km

### ambient conditions

ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> <li>note</li> </ul>	-40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40 (when installed)

### design, dimensions and weights

design	Media module
width	110 mm
height	22 mm
depth	91 mm
net weight	0.43 kg
product feature / conformal coating	Yes
fastening method	screwed
<ul style="list-style-type: none"> <li>installation in media module slot</li> </ul>	Yes

### standards, specifications, approvals

standard	
<ul style="list-style-type: none"> <li>for EMC</li> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	FCC Part 15 (Class A), EN55022 (CISPR22 Class A) UL 60950-1, CSA C22.2 No. 60950-7 Hazardous Locations: Class 1 Division 2 EN 61000-6-4 (Class A) EN 61000-6-2

laser protection class	21 CFR Chapter 1, Subchapter J
certificate of suitability	EN 61000-6-2, EN 61000-6-10
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• C-Tick</li> <li>• KC approval</li> <li>• E1 approval</li> <li>• IEC 61850-3</li> </ul>	Yes No No No Yes

**standards, specifications, approvals / Environmental Product Declaration**

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> <li>• total</li> <li>• during manufacturing</li> <li>• during operation</li> <li>• after end of life</li> </ul>	259.55 kg 13.3 kg 246.21 kg 0.04 kg

**further information / internet links**


internet link	
<ul style="list-style-type: none"> <li>• to website: Selection guide for cables and connectors</li> <li>• to website: Industry Mall/RUGGEDCOM selector</li> <li>• to website: Industrial communication</li> <li>• to website: Siemens RUGGEDCOM</li> <li>• to web page: SiePortal</li> <li>• to website: Image database</li> <li>• to website: CAx-Download-Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/ruggedcom-selector">https://www.siemens.com/ruggedcom-selector</a> <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a> <a href="https://www.siemens.com/ruggedcom">https://www.siemens.com/ruggedcom</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**security information**

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>
----------------------	---

**Approvals / Certificates**

General Product Approval	other	Environment
--------------------------	-------	-------------

<a href="#">Manufacturer Declaration</a>	<a href="#">inspection certificate</a>	
--	--	---

last modified: 11/14/2025 