

RUGGEDCOM RX1500PN M12 CG03B Line Module M12 Copper Ethernet Modules 2x 10/100/1000TX 8-pin M12 with controlled Bypass Conformal Coating

| | |
|--|--|
| Technical Product Detail Page | https://i.siemens.com/1P6GK6015-0AL20-0PE1 |
| suitability for operation | RX1500, RX1501, RX1510, RX1511, RX1512 |
| interfaces | |
| number of electrical/optical connections / for network components or terminal equipment / maximum | 2 |
| number of electrical connections <ul style="list-style-type: none"> for network components or terminal equipment / maximum | 2 |
| number of 10/100/1000 Mbit/s M12 ports | 2 |
| type of electrical connection <ul style="list-style-type: none"> for network components or terminal equipment | M12 |
| ambient conditions | |
| ambient temperature <ul style="list-style-type: none"> during operation during storage during transport note | -40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP40 |
| design, dimensions and weights | |
| design | Media module |
| width | 20 mm |
| height | 115 mm |
| depth | 180 mm |
| net weight | 0.35 kg |
| product feature / conformal coating | Yes |
| fastening method <ul style="list-style-type: none"> installation in media module slot | screwed Yes |
| standards, specifications, approvals | |
| standard <ul style="list-style-type: none"> for EMC for safety / from CSA and UL for hazardous zone / from CSA and UL for emitted interference for interference immunity | FCC Part 15 (Class A), EN55022 (CISPR22 Class A) UL 60950-1, CSA C22.2 No. 60950-7 Hazardous Locations: Class 1 Division 2 EN 61000-6-4 (Class A) EN 61000-6-2 |
| certificate of suitability <ul style="list-style-type: none"> CE marking C-Tick KC approval E1 approval railway application in accordance with EN 50155 railway application in accordance with EN 50124-1 IEC 61850-3 | EN 61000-6-2, EN 61000-6-10 Yes No No No Yes Yes Yes |
| standards, specifications, approvals / Environmental Product Declaration | |
| Environmental Product Declaration | Yes |
| global warming potential [CO2 eq] <ul style="list-style-type: none"> total during manufacturing | 259.55 kg 13.3 kg |

- during operation
- after end of life

246.21 kg
0.04 kg

further information / internet links

internet link

- to website: Selection guide for cables and connectors
- to website: Industry Mall/RUGGEDCOM selector
- to website: Industrial communication
- to website: Siemens RUGGEDCOM
- to web page: SiePortal
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/109766358>
<https://www.siemens.com/ruggedcom-selector>
<https://www.siemens.com/simatic-net>
<https://www.siemens.com/ruggedcom>
<https://sieportal.siemens.com/>
<https://www.automation.siemens.com/bilddb>
<https://www.siemens.com/cax>
<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

other

Environment

[Manufacturer Declaration](#)



EG-Konf.

[inspection certificate](#)



last modified:

11/14/2025