

product type designation

MDS D100 transponder

transponder MDS D100 for RF200/RF300 ISO/MOBY D ISO card PETix up to +80 °C ISO 15693 chip type, NXP ICODE SLI, 112 byte user memory; 85x 54x 0.8 mm (LxWxH); minimum order quantity 50 units



suitability for operation

RF200, RF300, MOBY D

Technical Product Detail Page

<https://l.siemens.com/1P6GT2600-0AD10>

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	650 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	ISO 15693
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	Yes

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	EEPROM
storage capacity / of the user memory	112 byte
type of memory organization	UID (fixed code) 8 bytes, user memory 112 bytes, configuration memory 8 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1E+14
number of write cycles / at ambient temperature < 40 °C / maximum	100000
data retention time / at ambient temperature < 40 °C / not less than	10 a
property of memory	Block-by-block write protection of the user memory
type of transponder chip used	NXP I-Code SLI

mechanical data

material	PET laminated plastic
color	white / petrol
mounting distance / relating to metal surfaces / recommended / minimum	20 mm

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	<p>-25 ... +80 °C</p> <p>-25 ... +80 °C</p> <p>-25 ... +80 °C</p>
protection class IP	IP68
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
resistance to mechanical stress	Shock and vibration according to ISO 10373 / ISO 7810, torsion and twisting according to ISO 10373 / ISO 7816-1

design, dimensions and weights

width	54 mm
-------	-------

height	0.9 mm
depth	85.6 mm
net weight	5 g
fastening method	gluing, mounting bag (see accessories)

product features, product functions, product components / general

product feature	
• printable	Yes
printing process	Printable on both sides

standards, specifications, approvals

certificate of suitability	
• IECEx	No
MTBF	228 a

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	0.93 kg
• during manufacturing	0.88 kg
• during operation	0.00041 kg
• after end of life	0.05 kg

accessories

accessories	Fixing strap, holder, spacer
-------------	------------------------------

further information / internet links

internet link	
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to web page: identification and localization systems	https://www.siemens.com/ident
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAx-Download-Manager	https://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
----------------------	---

Approvals / Certificates

General Product Approval



[China RoHS](#)

[Manufacturer Declaration](#)

General Product Approval	EMV	Environment
--------------------------	-----	-------------

[Miscellaneous](#)

[KC](#)



last modified:

11/13/2025 