

### product type designation



### MDS D522 transponder for screwing

Transponder MDS D522 only for RF200/RF300 Gen2 For screwing into metal, ISO 15693, chip type Fujitsu MB89R112, 8192 bytes FRAM user memory 20x 6 mm(DxH); M20x 1 thread minimum order quantity 5 units.

### suitability for operation

RF200, RF300

### Technical Product Detail Page

<https://l.siemens.com/1P6GT2600-5AF00>

### radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	35 mm; range is reader dependent: observe <a href="http://support.automation.siemens.com/WW/view/en/67384964">http://support.automation.siemens.com/WW/view/en/67384964</a>
protocol / with radio transmission	ISO 15693
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	Yes

### electrical data

product component / backup battery	No
------------------------------------	----

### memory

type of memory	FRAM
storage capacity / of the user memory	8192 byte
type of memory organization	UID (fixed code) 8 bytes, user memory 8192 bytes, configuration memory 40 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1E+12
number of write cycles / at ambient temperature < 40 °C / maximum	1E+12
data retention time / at ambient temperature < 40 °C / not less than	10 a
property of memory	Block-by-block write protection of the user memory
type of transponder chip used	Fujitsu MB89R112

### mechanical data

material	PA6.6 GF / brass, nickel-plated
color	black / silver
tightening torque / of the screw for securing the equipment / maximum	1 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

### ambient conditions

ambient temperature	
<ul style="list-style-type: none"> <li>during read/write access</li> <li>outside the read/write area</li> <li>during storage</li> </ul>	<p>-25 ... +85 °C</p> <p>-40 ... +100 °C</p> <p>-40 ... +100 °C</p>
protection class IP	IP68
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	500 m/s <sup>2</sup>
vibrational acceleration	200 m/s <sup>2</sup>

design, dimensions and weights	
height	6 mm
diameter	20 mm
net weight	13 g
fastening method	Thread M20 x 1, glue

product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
<ul style="list-style-type: none"> <li>printable</li> </ul>	No

standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> <li>IECEX</li> </ul>	No
MTBF	228 a

further information / internet links	
internet link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to web page: identification and localization systems</li> <li>to web page: SiePortal</li> <li>to website: Image database</li> <li>to website: CAX-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/ident">https://www.siemens.com/ident</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>

### Approvals / Certificates

#### General Product Approval



EG-Konf.



CCC



[China RoHS](#)

[Manufacturer Declaration](#)

#### EMV

[KC](#)

last modified:

11/13/2025