

product type designation

RF360T transponder

SIMATIC RF300 Transponder RF360T EPOXY card, 8 KB FRAM, IP67, -25 to +70 °C, 85x 54x 2.5 mm, Minimum order quantity 10 units



suitability for operation

RF300

Technical Product Detail Page

<https://l.siemens.com/1P6GT2800-4AC00>

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	150 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300-specific
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	Yes

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	FRAM / EEPROM
storage capacity / of the user memory	8189 byte
type of memory organization	UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes
number of read cycles / at ambient temperature < 40 °C / maximum	1E+10
number of write cycles / at ambient temperature < 40 °C / maximum	1E+10
data retention time / at ambient temperature < 40 °C / not less than	10 a
property of memory	Block-by-block write protection of the OTP memory

mechanical data

material	Epoxy resin
color	anthracite
mounting distance / relating to metal surfaces / recommended / minimum	20 mm

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	<p>-25 ... +75 °C</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>
protection class IP	IP67
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
resistance to mechanical stress	Continuous torsion and bending stress not permissible

design, dimensions and weights

width	55 mm
-------	-------

height	2.5 mm
depth	86 mm
net weight	25 g
fastening method	2 x M3 screws, mounting bag (see accessories)

product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> • silicon-free 	Yes
<ul style="list-style-type: none"> • printable 	No

standards, specifications, approvals

certificate of suitability	
<ul style="list-style-type: none"> • IECEx 	No
<ul style="list-style-type: none"> • cULus approval 	Yes
MTBF	1200 a

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> • total 	0.93 kg
<ul style="list-style-type: none"> • during manufacturing 	0.88 kg
<ul style="list-style-type: none"> • during operation 	0.00041 kg
<ul style="list-style-type: none"> • after end of life 	0.05 kg

accessories

accessories	Fixing strap, spacer
-------------	----------------------

further information / internet links

internet link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to web page: identification and localization systems • to web page: SiePortal • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	https://www.siemens.com/tstcloud https://www.siemens.com/ident https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com

security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
----------------------	---

Approvals / Certificates

General Product Approval



[China RoHS](#)

[Manufacturer Declaration](#)

General Product Approval	EMV	Environment
--------------------------	-----	-------------

[Miscellaneous](#)

[KC](#)



last modified:

11/13/2025 