



SIMATIC RF600 Reader RF690R CMITT; interface Ethernet RJ45 PoE 4 antennas, 1 digital input/ 1 digital output, 24 V DC; -25 to +55 °C; without accessories and antennas.

Technical Product Detail Page

<https://i.siemens.com/1P6GT2811-7AD20-2AA0>

suitability for operation

RFID high-performance reader for use in the warehouse environment for recording high flows of goods.

### radio frequencies

operating frequency	920 ... 925 MHz
transmit power	3 ... 2000 mW
effective radiated power	
• for each external antenna / maximum	2000 mW
equivalent isotropically radiated power	
• for each external antenna / maximum	4000 mW
range / maximum	10 m; Extended ranges possible, see RF600 System Manual, Range table: <a href="http://support.automation.siemens.com/WW/view/en/67384964">http://support.automation.siemens.com/WW/view/en/67384964</a>
protocol / with radio transmission	EPCglobal Class 1 Gen 2 V2 / ISO/IEC 18000-62
transfer rate / with radio transmission / maximum	640 kbit/s
product feature / multitag-capable	Yes

### interfaces

number of external antennas	4
standard for interfaces / for communication	Ethernet, OPC UA, XML
type of electrical connection	
• for external antenna(s)	RP-TNC
• for supply voltage	terminal block, 4-pole
• at the digital inputs/outputs	RJ45 connector (8-pole)
number of digital inputs	1
number of digital outputs	1

### mechanical data

material	Lexan
color	silver, TI-Grey
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

### supply voltage, current consumption, power loss

supply voltage / at DC	
• rated value	24 V
•	20 ... 30 V
consumed current / at DC	
• at 24 V / typical	2 A
• at 24 V / maximum	2 A

### ambient conditions

ambient temperature	
• during operation	-25 ... +55 °C
• during storage	-40 ... +85 °C

<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +85 °C
ambient condition / for operation	With operating temperature below -20 °C: Warming-up time at least 10 minutes
protection class IP	IP33
shock resistance	EN 60068-2-27, EN 60068-2-6
shock acceleration	250 m/s <sup>2</sup>
vibrational acceleration	30 m/s <sup>2</sup>
resistance to mechanical stress	The maximum values for shock and vibration acceleration must not occur as continuous stress and they apply exclusively to assembly using screws
<b>design, dimensions and weights</b>	
width	245 mm
height	209 mm
depth	41 mm
net weight	1.3 kg
fastening method	Vesa 100 with 4 screws, DIN rail, mounting hole 4 x M4 screws
wire length	
<ul style="list-style-type: none"> <li>of antenna cable / minimum</li> <li>of antenna cable / maximum</li> </ul>	1 m 40 m
<b>product features, product functions, product components / general</b>	
display version	3 LEDs
protocol / is supported / Media Redundancy Protocol (MRP)	No
product function / of the PROFINET IO device / is supported / H-Sync forwarding	No
protocol / is supported	
<ul style="list-style-type: none"> <li>LLDP</li> <li>PROFINET IO protocol</li> <li>TCP/IP</li> <li>SNMP v1</li> <li>SNMP v2</li> <li>SNMP v3</li> <li>DCP</li> <li>EtherNet/IP protocol</li> <li>OPC UA</li> </ul>	No No Yes Yes No Yes Yes No Yes
product feature / silicon-free	Yes
<b>product functions / management, configuration, engineering</b>	
type of parameterization	WBM
type of programming	OPC UA, XML
type of computer-switched communication	TCP/IP
<b>standards, specifications, approvals</b>	
certificate of suitability	wireless acc. to CMIIT, OPC UA: embedded UA Server Profile
certificate of suitability	
<ul style="list-style-type: none"> <li>IECEX</li> </ul>	No
MTBF	28 a
<b>standards, specifications, approvals / Environmental Product Declaration</b>	
Environmental Product Declaration	Yes
global warming potential [CO <sub>2</sub> eq]	
<ul style="list-style-type: none"> <li>total</li> <li>during manufacturing</li> <li>during operation</li> <li>after end of life</li> </ul>	289.45 kg 40 kg 249 kg 0.45 kg
<b>accessories</b>	
accessories	up to 4 external antennas, set for mounting on top-hat rail or profile rail
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>to website: Selection guide for cables and connectors</li> <li>to web page: selection aid TIA Selection Tool</li> <li>to web page: RFID country approval</li> <li>to web page: identification and localization systems</li> <li>to web page: SiePortal</li> <li>to website: Image database</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/rfid-approvals">https://www.siemens.com/rfid-approvals</a> <a href="https://www.siemens.com/ident">https://www.siemens.com/ident</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>

- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://www.siemens.com/cax>

<https://support.industry.siemens.com>

### security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](http://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

### Approvals / Certificates

General Product Approval

Environment

[China RoHS](#)



last modified:

11/13/2025