

### product type designation



### RF240R reader ASCII

SIMATIC RF200 Reader RF240R; RS-232 interface (ASCII/scan mode); IP67, -25 to +70 °C; 50x 50x 30 mm; with integrated antenna.

Technical Product Detail Page

<https://l.siemens.com/1P6GT2821-4AC40>

suitability for operation

ISO 15693 transponder (MDS Dxxx), for connecting to PC and control systems (incl. Scan Mode)

### radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	65 mm; Range is dependent on transponder type: observe <a href="http://support.automation.siemens.com/WW/view/en/67384964">http://support.automation.siemens.com/WW/view/en/67384964</a>
protocol / with radio transmission	ISO 15693, ISO 18000-3
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	No

### electrical data

transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
transmission time / for user data	
• for write access / per byte / typical	1.2 ms
• for read access / per byte / typical	1.2 ms

### interfaces

standard for interfaces / for communication	RS232
type of electrical connection	M12, 8-pin

### mechanical data





material	PA6.6
color	anthracite
tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

### supply voltage, current consumption, power loss

supply voltage / at DC	
• rated value	24 V
•	20.4 ... 28.8 V
consumed current / at DC	
• at 24 V / typical	0.05 A

### ambient conditions

ambient temperature	
• during operation	-20 ... +70 °C
• during storage	-25 ... +80 °C
• during transport	-25 ... +80 °C
protection class IP	IP67
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	500 m/s <sup>2</sup>

vibrational acceleration	200 m/s <sup>2</sup>				
<b>design, dimensions and weights</b>					
width	50 mm				
height	30 mm				
depth	50 mm				
net weight	0.06 kg				
fastening method	2 x M5 screws				
wire length					
• with RS 232 interface / maximum	30 m				
<b>product features, product functions, product components / general</b>					
display version	3-color LED				
product feature / silicon-free	Yes				
<b>standards, specifications, approvals</b>					
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus				
certificate of suitability					
• IECEX	No				
MTBF	430 a				
<b>standards, specifications, approvals / Environmental Product Declaration</b>					
Environmental Product Declaration	Yes				
global warming potential [CO2 eq]					
• total	50.4 kg				
• during manufacturing	10.7 kg				
• during operation	39.4 kg				
• after end of life	0.3 kg				
<b>further information / internet links</b>					
internet link					
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>				
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>				
• to web page: RFID country approval	<a href="https://www.siemens.com/rfid-approvals">https://www.siemens.com/rfid-approvals</a>				
• to web page: identification and localization systems	<a href="https://www.siemens.com/ident">https://www.siemens.com/ident</a>				
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>				
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>				
• to website: CAX-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>				
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>				
<b>security information</b>					
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)				
<b>Approvals / Certificates</b>					
<b>General Product Approval</b>					
				<a href="#">China RoHS</a>	<a href="#">Manufacturer Declaration</a>
EMV	Radio Equipment	Environment			

[KC](#)

[Miscellaneous](#)



---

last modified:

11/13/2025