

product type designation

Wide-range power supply unit with US connecting cable

SIMATIC RF600 wide-range voltage supply for SIMATIC RF systems In: AC: 100-240 V Out: 24 V DC 3 A CE, UL, CSA degree of protection IP67 with power supply cable / connector US consisting of: 1x 6GT28980AC81 1x 6GT28980AC21.



type of current supply

Input: 100 to 230 V AC, output: 24 V DC / 3 A

Technical Product Detail Page

<https://l.siemens.com/1P6GT2898-0AC20>

suitability for use

Two readers can be connected directly. Robust and cast industrial power supply unit with high degree of protection for use directly at the process.

electrical data / input

voltage curve / at input

AC single phase

supply voltage / 1 / rated value

230 V

- supply voltage / 1 / rated value

100 ... 240 V

line frequency

- 50 Hz
- 60 Hz

Yes
Yes

electrical data / output

voltage curve / at output

DC 24 V fixed voltage

output voltage

- 1 / at DC / rated value

24 V

output current

- rated value
- rated range

3 A
0 ... 3.9 A

efficiency in percent

90 %

electrical data / closed-loop control

relative overall tolerance / of the voltage

2 %

electrical data / protection and monitoring

design of the overvoltage protection / at output

U_{out} nom +20 % typ.

property of the output / short-circuit proof

Yes

design of short-circuit protection

Permanent

enduring short circuit current / RMS value / maximum

3.9 A

electrical data / safety

galvanic isolation / between input and output

Yes

galvanic isolation

SELV / PELV according to EN 60950

operating resource protection class

Class II (protective insulation)

interfaces

number of electrical connections

- for power supply

2

type of electrical connection

- at input
- at output

US plug with 2 m connecting cable
2 x M12 4 pin, A-coded, female

signal inputs/outputs

product component / signaling contact

No

| design, dimensions and weights | |
|---|---|
| width | 85 mm |
| height | 35 mm |
| depth | 175 mm |
| net weight | 0.96 kg |
| fastening method | 4 screws M5 |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation during storage during transport note | -25 ... +75 °C -40 ... +85 °C -40 ... +85 °C free convection |
| protection class IP | IP67 |
| standards, specifications, approvals | |
| standard | |
| <ul style="list-style-type: none"> for safety / from CSA and UL for emitted interference | EN 60950 / UL 60950 / CAN/CSA 22.2 950, 3 Edition EN 61000-6-3, EN 55011 (Class B) |
| accessories | |
| accessories / included | Power supply un...T2898-0AC003 |
| further information / internet links | |
| internet link | |
| <ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to web page: SiePortal to website: Image database to website: CAx-Download-Manager to website: Industry Online Support | https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com |
| security information | |
| security information | <p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p> |

Approvals / Certificates

General Product Approval



last modified:

11/11/2025