

Data sheet for Output reactor

Article No. : 6SL3000-2BE33-8AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :




Figure similar

Rated data

| | |
|---------------|----------|
| Rated current | 380.00 A |
| Power loss | 0.500 kW |

Mechanical data

| | |
|----------------------|-------------------|
| Degree of protection | IP00 |
| Net weight | 73 kg (160.94 lb) |

Dimensions

| | |
|--------|-------------------|
| Width | 300 mm (11.81 in) |
| Height | 285 mm (11.22 in) |
| Depth | 277 mm (10.91 in) |

Connections

Power connection Power Module

| | |
|---------|----------------------------------|
| Version | flat connector for cable lug M10 |
|---------|----------------------------------|

Power connection motor

| | |
|---------|-------------------------------------|
| Version | Flange connection for cable lug M10 |
|---------|-------------------------------------|

Max. motor cable length

3 AC 380 V -10 % ... 400 V

| | |
|------------|-------|
| Shielded | 300 m |
| Unshielded | 450 m |

3 AC 401 V ... 480 V +10 %

| | |
|------------|-------|
| Shielded | 300 m |
| Unshielded | 450 m |

PE connection

| | |
|---------|----------|
| Version | M8 Screw |
|---------|----------|