

## Data sheet for Braking Module

Article No. : 6SL3300-1AF32-5AA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

Rated power $P_{DB}$	50.00 kW
Rated power, max.	250.00 kW
Activation threshold	967 V (841 V)
	adjustable via DIP switch

### General technical specifications

DC link voltage	DC 675 ... 900 V
-----------------	------------------

### Mechanical data

Net weight	7.3 kg (16.09 lb)
------------	-------------------

### Digital inputs

Number	1
Voltage	24 V
Low level	-3 V ... 5 V
High level	15 V ... 30 V
Power consumption at 24 V DC, typ.	10 mA

### Digital outputs

Number	1
Voltage	DC 24 V
Load current per digital output, max.	500 mA

### Connections

#### Digital inputs

Connection cross-section, max.	1.5 mm <sup>2</sup> (16 AWG)
--------------------------------	------------------------------

#### Digital outputs

Connection cross-section, max.	1.5 mm <sup>2</sup> (16 AWG)
--------------------------------	------------------------------

#### PE connection

Version on housing	M8 nut
--------------------	--------

#### BrakeResistor

Connection cross-section, max.	50.0 mm <sup>2</sup> (1 AWG)
--------------------------------	------------------------------