

## Data sheet for SINAMICS S220 Motor Module

Article No. : 6SL5120-1UE22-4AD0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Rated data	
<b>Input</b>	
DC link voltage	DC 495 ... 720 V
DC-link current	30.0 A
<b>Output</b>	
Rated power IEC	11.0 kW
Rated power NEC	15.0 hp
<b>Output current</b>	
Rated value $I_N$	24.0 A
Maximum current $I_{max}$	72.0 A
For S6 duty (40%) $I_{S6}$	72.0 A
Rated pulse frequency	4 kHz
Pulse frequency, max.	16 kHz
<b>Current carrying capacity</b>	
DC link busbars <sup>1)</sup>	100 A
24 V busbars	20 A
DC link capacitance	390 $\mu$ F
Output frequency for servo control <sup>2)</sup>	0 ... 650 Hz
Output frequency for V/f control <sup>3)</sup>	0 ... 600 Hz
Output frequency for vector control <sup>4)</sup>	0 ... 300 Hz

Electronics power supply	
Voltage	24V (20.4 ... 28.8 V) -15% / +20%
Power loss, typ.	1.00 A (External 24 V power supply required)

General tech. specifications	
Efficiency $\eta$	0.98
Sound pressure level (1m)	75 dB
Power loss (typical)	189.00 W

Inputs / outputs	
<b>Fail-safe digital inputs</b>	
Number	1 (for enable pulse function)
Type	Type 1 and type 3
Design	Optocoupler (up to 60 V)

Ambient conditions	
Cooling	Air cooling using an integrated fan
Cooling air requirement	33 m <sup>3</sup> /h (0.3 ft <sup>3</sup> /s)
Installation altitude (without derating)	1,000 m (13,123.00 ft)
<b>Relative humidity</b>	
Operation	5 ... 95%
Transport	5 ... 95%
Storage	5 ... 95%
<b>Ambient temperature</b>	
Operation	-10 ... 55 °C (14 ... 131 °F)
Transport	-25 ... 70 °C (-13 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)

Connections	
<b>Signal cable</b>	
Type	Plug-in terminal connection
Conductor cross-section <sup>5)</sup>	0.2 ... 1.5 mm <sup>2</sup> (23 ... 16 AWG)
<b>Motor end</b>	
Type	Connection plug with screw terminal or push-in
Conductor cross-section	0.8 ... 6.0 mm <sup>2</sup> (19 ... 9 AWG)
Number of connections	1
<b>DC link</b>	
Type	Busbar connection
Number of connections	2
<b>PE connection</b>	
Type <sup>7)</sup>	Screw terminal; M5, max. 12 mm wide/ TX 25
Conductor cross-section	0.75 ... 6.0 mm <sup>2</sup> (19 ... 9 AWG)
<b>Holding brake</b>	
Type	X21 connection plug
Conductor cross-section	0.75 ... 6.0 mm <sup>2</sup> (9 ... 19 AWG)
Number of connections	1
<b>Max. motor cable length</b>	
Shielded	70 m (230.00 ft)
Unshielded	105 m (344.00 ft)

Mechanical data	
Degree of protection	IP20 / UL open type
Net weight	4.7 kg (10.36 lb)
<b>Dimensions</b>	
Width	50 mm (1.97 in)
Depth	270 mm (10.63 in)
Height	380 mm (14.96 in)
Height including shield plate	419.0 mm (16.50 in)

Certificates	
Certificate of suitability	CE, cULus (UL 61800-5-1, CSA 22.2 No. 274), KC, EAC, UKCA
Verification of suitability for fail-safety	SIL 2 according to IEC 61508 and IEC 61800-5-2, PL d according to ISO 13849-1, Category 2 according to ISO 13849-1

<sup>1)</sup>200 A with 6 mm DC link bridges; connection via DC link adapter (both accessories)

<sup>2)</sup>Note the correlation between the max. output frequency, pulse frequency and current derating. The output frequency is currently limited to 550 Hz. The specified value applies to systems with supplementary license.

<sup>3)</sup>Observe the dependency between max. output frequency and current derating.

<sup>4)</sup>Note the correlation between the max. output frequency, pulse frequency and current derating. The output frequency is currently limited to 550 Hz. The specified value applies to systems with supplementary license.

<sup>5)</sup>0.75 mm<sup>2</sup> for flexible cables with protective collar

<sup>7)</sup>Protective conductor of the Motor Module