

Data sheet for SINAMICS S200

Article No. : 6SL5510-1BB10-1AF0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input

Number of phases	1/3 AC
Line voltage	200 ... 240 V +10 % - %
Line frequency	45 ... 66 Hz
Rated current for 1 phase	1.2 A
Rated current for 3 phases	1.0 A
Inrush current	10.5 A

Output

Number of phases	3 AC
Rated power	0.10 kW
Rated current I_N	0.8 A
Max. output current	3.3 A
Pulse frequency	8 kHz
Output frequency	0 ... 550 Hz

Electronics power supply

Voltage	20.4 ... 28.8 V
Current demand, max.	0.7 A

Control Type

Communication	PROFINET
---------------	----------

Ambient conditions

Cooling	natural convection
Installation altitude (without derating)	4,000 m
Installation altitude	1,000 m (3,281.00 ft)

Ambient temperature during

Operation	0 ... 55 °C (32 ... 131 °F)
Maximum without power reduction	45 °C
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity during

Max. operation	95 %
----------------	------

Data sheet for SINAMICS S200

Article No. : 6SL5510-1BB10-1AF0

Inputs / outputs

Standard digital inputs

Number	4
--------	---

Fail-safe digital inputs

Number	2
--------	---

Rapid input digital inputs

Number	2
--------	---

Digital outputs

Number	2
--------	---

Mechanical data

Degree of protection	IP20 / UL open
----------------------	----------------

Frame size	FSA
------------	-----

Net weight	1.00 kg (1.98 lb)
------------	-------------------

Dimensions

Width	40.0 mm (1.57 in)
-------	-------------------

Height	170.0 mm (6.69 in)
--------	--------------------

Depth	135.0 mm (5.31 in)
-------	--------------------

Connections

Signal cable

Version	MDR plug
---------	----------

Line side

Version	Push-in connection
---------	--------------------

Conductor cross-section	0.75 ... 2.50 mm ² / ... AWG
-------------------------	---

Motor end

Version	Push-in connection
---------	--------------------

Conductor cross-section	0.75 ... 2.50 mm ² / ... AWG
-------------------------	---

DC link (for braking resistor)

Version	Push-in connection
---------	--------------------

Conductor cross-section	0.75 ... 2.50 mm ² / 19 ... 13 AWG
-------------------------	---

Cable length	3.00 m (10)
--------------	-------------

PE connection

Conductor cross-section	0.75 ... 2.50 mm ²
-------------------------	-------------------------------

Holding brake

Version	Push-in connection
---------	--------------------

Conductor cross-section	0.00 ... 2.00 mm ² / 23 ... 16 AWG
-------------------------	---

STO connection

Version	Push-in connection
---------	--------------------

Conductor cross-section	0.00 ... 2.00 mm ² / 24 ... 16 AWG
-------------------------	---

encoder connection

Version	plug connector IX Typ C
---------	-------------------------

Max. motor cable length

Shielded	30 m
----------	------

Certificates

Certificate of suitability

CE marking

EMC Directive 2014/30/EU with IEC 61800-3, Low-Voltage Directive 2014/35/EU, Machinery Directive 2006/42/EC, RoHS 2011/65/EU, WEE 2012/19/EU

Verification of suitability for fail-safety

SIL 3 according to IEC 61508 and IEC 61800-5-2, PL e according to ISO 13849-1, Category 3 or 4 according to ISO 13849-1

Data sheet for SINAMICS S200

Article No. : 6SL5510-1BB10-1AF0

Environmental conditions

Chemically active substances

Operation	Class 3C2 according to EN 60721-3-3: 2002
Transport	Class 2C2 according to IEC 60721-3-2:1997
Storage	Class 1C2 according to IEC 60721-3-1: 1997

Biologically active substances

Operation	Class 3B1, acc. to EN 60721-3-3: 2002, dust not permitted
Storage	Class 1B1 according to IEC 60721-3-1:1997

Mechanically active substances

Operation	Class 3S2 according to IEC 60721-3-3: Ed. 2.2 2002
-----------	--

Climatic environmental conditions

Operation	Class 3K3 according to IEC 60721-3-3 Ed. 2.2: 2002
Transport	Class 2K4 according to IEC 60721-3-2:1997
Storage	Class 1K4 according to IEC 60721-3-1:1997

Mechanical environmental conditions

Operation	Class 3M1 according to IEC 60721-3-3 Ed. 2.2: 2002
Transport	Class 2M3 according to IEC 60721-3-2:1997
Storage	Class 1M2 according to IEC 60721-3-1:1997