

product type designation

product description

ITP Standard Cable GP for Industrial Ethernet

Industrial twisted pair cable (4-core), sold by the meter, unassembled

ITP Standard Cable for Industrial Ethernet J-02YSCY 2x2X0.64/1.5 PIMF F, installation cable 2x2-core for on-site assembly of connector, non-assembled, Sold by the meter Minimum order quantity: 20 m delivery unit: max. 1000 m.



Technical Product Detail Page

<https://l.siemens.com/1P6XV1850-0AH10>

suitability for use

Used in the construction of Industrial Twisted Pair (ITP) networks

cable designation

J-02YSCY 2x2x0,64/1,5 PIMF F GN

wire length

sold by the meter

electrical data

attenuation factor per length

- at 10 MHz / maximum 0.057 dB/m
- at 100 MHz / maximum 0.18 dB/m
- at 300 MHz / maximum 0.31 dB/m

impedance

- at 1 MHz ... 100 MHz 100 Ω
- at 100 MHz ... 300 MHz 100 Ω

relative symmetrical tolerance

- of the characteristic impedance at 1 MHz ... 100 MHz 15 %
- of the characteristic impedance at 100 MHz ... 300 MHz 45 %

transfer impedance per length / at 10 MHz

2 mΩ/m

loop resistance per length / maximum

124 mΩ/m

insulation resistance coefficient

5000 GΩ·m

operating voltage

- RMS value 165 V
- maximum 225 V

mechanical data

number of electrical cores

4

design of the shield

Overlapped aluminum-clad foil (for each core), sheathed in an overall braided shield of tin-plated copper wires

core diameter

- of AWG22 insulated conductor 0.64 mm

outer diameter

- of inner conductor 0.64 mm
- of the wire insulation 1.5 mm

width / of cable sheath

9.2 mm

symmetrical tolerance of width / of cable sheath

0.5 mm

thickness / of cable sheath

6 mm

symmetrical tolerance of thickness / of cable sheath

0.5 mm

material

- of the wire insulation polyethylene (PE)
- of cable sheath PVC

color	
<ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	white/blue, white/orange green
bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	30 mm 45 mm
tensile load / maximum	80 N
weight per length	96 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-40 ... +70 °C -40 ... +70 °C -40 ... +70 °C -40 ... +70 °C
fire behavior	flame resistant according to IEC 60332-1
chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease 	oil resistant according to IEC 60811-2-1 (4 h / 70°C) Conditional resistance
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	No Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	No
UL/ETL style / 600 V Rating	No
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • CE marking 	Yes Yes
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	No No No No No No No
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under

Approvals / Certificates

General Product Approval



[Declaration of Con-
formity](#)



[Manufacturer Declara-
tion](#)

[China RoHS](#)

General Product Approval



last modified:

10/28/2025 