

product type designation

IWLAN RCoax Cable 2 GHz

IWLAN RCoax cable PE 1/2 2.4 GHz long distance -40 °C/+85 °C ext. temperature range. Sold by the meter minimum order quantity 20 m delivery unit: max. 500 m.



Technical Product Detail Page

<https://i.siemens.com/1P6XV1875-2A>

suitability for operation

For example, suspended monorails, cranes, stacker cranes. Line is water-repellent, resistant to microbes, and extremely resistant to many cleaning agents and disinfectants (such as iodophors, peroxyacetic acids (1% solution), and quaternary ammonium cations). Cleaning with high-pressure cleaner up to 50 kg.

### radio frequencies

operating frequency

- for WLAN in 2.4 GHz frequency band

2.4 ... 2.485 GHz

### electrical data

impedance

50 Ω

attenuation factor per length

- at 2.4 GHz / with cable mounted 10 mm above concrete / at 20 °C
- at 2.4 GHz / with cable mounted 15 mm above aluminum rail / at 20 °C

0.15 dB/m

0.17 dB/m

coupling attenuation

- at 2.4 GHz / at 20 °C
- note

35 dB

c(50) for distance of 10 cm between antenna and cable

capacity per length

76 pF/m

DC resistance per length

- of inner conductor / at 20 °C
- of coaxial line conductor / at 20 °C

1.48 Ω/km

2.8 Ω/km

relative speed

88 %

### mechanical data

outer diameter

- of inner conductor
- of dielectric
- of cable sheath

4.8 mm

12.4 mm

15.5 mm

thickness / of cable sheath

1.3 mm

material

- of inner conductor
- of dielectric
- of coaxial line conductor
- of cable sheath

Copper clad aluminum

Polyethylene foam

Overlapping copper foil with the slot groups bonded to cable jacket

Halogen-free polyolefine

color / of cable sheath

pastel turquoise

bending radius

- with single bend / minimum permissible

200 mm

number of bending cycles

1

tensile load / maximum

1100 N

weight per length	0.232 kg/m
mounting distance	
<ul style="list-style-type: none"> <li>recommended</li> </ul>	0.5 m
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during installation</li> </ul>	-40 ... +85 °C -70 ... +85 °C -25 ... +60 °C
product feature / resistant to UV radiation	Yes
<b>standards, specifications, approvals</b>	
standard	
<ul style="list-style-type: none"> <li>for fire behavior               <ul style="list-style-type: none"> <li>corrosive gas emission</li> <li>smoke emission</li> <li>flame resistance</li> </ul> </li> </ul>	IEC 60754-2 IEC 60332-1 and IEC 60332-3 Cat. C IEC 61034
certificate of suitability	
<ul style="list-style-type: none"> <li>UL approval</li> </ul>	Yes
wireless approval	Current national approvals can be found on the Internet under <a href="http://www.siemens.com/funkzulassungen">www.siemens.com/funkzulassungen</a>
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>to website: Selection guide for cables and connectors</li> <li>to web page: selection aid TIA Selection Tool</li> <li>to web page: WLAN country approval</li> <li>to website: Industrial communication</li> <li>to web page: SiePortal</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/wireless-approvals">https://www.siemens.com/wireless-approvals</a> <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>

last modified:

11/11/2025 