

product type designation

product description

antenna connection cable N-Connect/RSMA plug/plug

Connecting cable for SIMATIC NET antennas, preassembled

N-Connect/ R-SMA male/male flexible connection cable pre-assembled, Length 5 m flexible connecting cable Access point antenna (RCoax and others).



Technical Product Detail Page

<https://l.siemens.com/1P6XV1875-5CH50>

suitability for use

Flexible connecting cable for connecting an antenna to an access point/client

wire length

5 m

electrical data

number of electrical connections

2

type of electrical connection

N-Connect/R-SMA male/male

transmission frequency

0 ... 6000 MHz

attenuation factor per length

- at 2.4 GHz / typical
- at 5.2 GHz / typical
- at 5.85 GHz / typical

0.53 dB/m
0.83 dB/m
0.89 dB/m

return loss

- minimum

23 dB

impedance

- rated value

50 Ω

capacity per length / at 1 kHz

82 pF/m

relative speed

82 %

mechanical data

design of the shield

Braided shield made of tin-plated copper wires

outer diameter

- of inner conductor
- of dielectric
- of cable sheath

1.4 mm
3.8 mm
6.3 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

thickness / of cable sheath

0.76 mm

material

- of inner conductor
- of dielectric
- of cable sheath

Cu
polyethylene foam
FRNC

color

- of cable sheath

pastel turquoise

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

32 mm
45 mm

tensile load / maximum

80 N

weight per length

75 kg/km

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport during installation 	-40 ... +80 °C -40 ... +80 °C -40 ... +80 °C -25 ... +80 °C
chemical resistance	
<ul style="list-style-type: none"> to mineral oil 	conditional resistance
radiological resistance / to UV radiation	resistant
protection class IP	IP68; when plugged in

product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> halogen-free silicon-free 	Yes Yes

standards, specifications, approvals

certificate of suitability	
<ul style="list-style-type: none"> EAC approval RoHS conformity fire protection in accordance with EN 45545-2 	Yes Yes No
<ul style="list-style-type: none"> standard / for fire behavior / flame resistance 	UL 1685 (Vertical tray), UL 1581 Sec. 1090 (H)

further information / internet links

internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: SiePortal to website: Image database to website: CAX-Download-Manager to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com

security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
----------------------	---

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[China RoHS](#)

last modified:

10/28/2025