

product description

SM glass fiber-optic cable, preferred length, preassembled

FO connection cable LC/SM; pre-assembled on both ends with 2x LC duplex plugs for connection of MRB85536M; length 50 m



Technical Product Detail Page

<https://i.siemens.com/1P6XV1883-7EN50>

suitability for use

Halogen-free cable (acc. to IEC 61034-1 / 61034-2 and IEC 60754-1 / IEC 60754-2) for use indoors and outdoors with permanent installation, UL approval

version of the assembled FO cable

pre-assembled with 2x LC DUPLEX connectors for connecting MRB85536M

cable designation

AT-V(ZN)HH 2E9/125 TB900L 2,2

wire length

50 m

optical data

attenuation factor per length

- at 1550 nm / maximum

0.22 dB/km

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

single-mode fiber 4E9/125/900, OS2

design of the FOC core

fixed core (TB900L)

design of the fiber-optic cable

segmentable

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

9 µm
125 µm
2.2 mm

symmetrical deviation / of the outer diameter of the FOC core sheath

0.1 mm

outer diameter / of the cable

7.2 mm

symmetrical deviation / of the outer diameter of the line

0.5 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass
Quartz glass
FRNC
FRNC
Aramid fibers

color

- of the FOC core sheath
- of cable sheath

orange/black
green

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

70 mm
105 mm

tensile load

- during installation / short-term
- during operation / maximum

800 N
250 N

short-term shear force per length

500 N/cm

weight per length	57 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport during installation 	-30 ... +85 °C -30 ... +85 °C -30 ... +85 °C -5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
class of burning behaviour / according to EN 13501-6	B2ca - s1a d1 a1
chemical resistance	
<ul style="list-style-type: none"> to mineral oil to grease to water 	no resistance conditional resistance conditional resistance
radiological resistance / to UV radiation	conditional resistance
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> halogen-free silicon-free 	Yes Yes
product component / rodent protection	No
wire length	
<ul style="list-style-type: none"> for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum for glass FOC / for 10GBaseLR / for Industrial Ethernet / maximum for glass FOC / with 10GBaseER / for Industrial Ethernet / maximum for glass FOC / with PROFIBUS / maximum 	26000 m 5000 m 10000 m 40000 m 15000 m
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> UL approval RoHS conformity 	Yes; c(UL)us OFNR FT4 Yes
further information / internet links	
internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to web page: SiePortal to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/simatic-net https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information / header	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#)



last modified:

11/11/2025 