



Figure similar

TRIP RELAY WITH 8 CHANGE OVER CONTACTS AUXILIARY VOLTAGE:  
110V/125V DC OPERATING TIME STANDARD, 20MS RELAIS WITH SOCKET  
7XP9010-3 FOR FLUSH MOUNTING

General technical data	
type of voltage	DC
continuous current	10 A
switching behavior	monostable
type of switching contact	bifurcated contact
design of the switching function / positively driven	Yes
response time	20 ms
Product details	
product component / LED	No
Product Functions	
manual RESET	No
Supply voltage	
supply voltage / at DC / rated value	125 V
Inputs / Outputs	
number of NC contacts	0
number of NO contacts	0
number of CO contacts	8
switching capacity active power / at DC / maximum	4 400 W
switching capacity active power / at DC / maximum / note	at 110V DC
Mechanical Design	
width	120 mm
height	80 mm
depth	122 mm
type of electrical connection	screw terminal
product feature / plug-in terminal blocks	No
design of the snap-on socket base	flush-mounting socket
Degree of protection / protection class	
protection class IP / on the front	IP40
protection class IP / rear side	IP10
Environmental conditions	
ambient temperature / during operation	-25 ... +70 °C
Further information	

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information- and Downloadcenter (catalogues, leaflets,...)**

<https://www.siemens.com/energy-automation>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7PA2632-0AA00-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7PA2632-0AA00-1>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7PA2632-0AA00-1](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7PA2632-0AA00-1)

**Tender specifications**

<https://www.siemens.com/specifications>

**Power Academy - Your training and consulting partner in the area of power transmission and distribution**

<https://www.siemens.com/poweracademy>

---

