



Figure similar

ANNUNCIATION RELAY WITH 4 LED INDICATIONS AND RESET PUSH BUTTON AUXILIARY VOLTAGE: 24/30V DC RELAIS WITH SOCKET 7XP9010-2 FOR FLUSH MOUNTING

| General technical data                                   |                       |
|--|-----------------------|
| type of voltage  | DC                    |
| continuous current                                       | 8 A                   |
| switching behavior                                       | monostable            |
| type of switching contact                                | bifurcated contact    |
| design of the switching function / positively driven     | Yes                   |
| response time  | 5 ms                  |
| Product details  |                       |
| product component / LED                                  | Yes                   |
| Product Functions  |                       |
| manual RESET   | Yes                   |
| Supply voltage   |                       |
| supply voltage / at DC / rated value                     | 30 V                  |
| Inputs / Outputs   |                       |
| number of NC contacts                                    | 0                     |
| number of NO contacts                                    | 4                     |
| number of CO contacts                                    | 4                     |
| switching capacity active power / at DC / maximum        | 1 650 W               |
| switching capacity active power / at DC / maximum / note | at 110V DC            |
| Mechanical Design  |                       |
| width  | 120 mm                |
| height   | 80 mm                 |
| depth  | 144.5 mm              |
| type of electrical connection                            | screw terminal        |
| design of the snap-on socket base                        | flush mounting socket |
| Degree of protection / protection class                  |                       |
| protection class IP / on the front                       | IP40                  |
| protection class IP / rear side                          | IP10                  |
| Environmental conditions                                 |                       |
| ambient temperature / during operation                   | -10 ... +55 °C        |
| Further information                                      |                       |

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information- and Downloadcenter (catalogues, leaflets,...)**

<https://www.siemens.com/energy-automation>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7TS1612-0AA00-1>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/7TS1612-0AA00-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7TS1612-0AA00-1](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7TS1612-0AA00-1)

Tender specifications

<https://www.siemens.com/specifications>

Power Academy - Your training and consulting partner in the area of power transmission and distribution

<https://www.siemens.com/poweracademy>

---

