

LRA0351-6-TX-F TERMINAL ELEMENT TX-F L1,L2,L3,N,PE 800A

Model	
product designation	feeder unit for LR busbar trunking system
operating voltage at AC	
<ul style="list-style-type: none"> at 50 Hz rated value maximum at 60 Hz rated value minimum at 60 Hz rated value maximum 	1 000 V 1 000 V 1 000 V
Protection class	
protection class IP	IP68
Main circuit	
operating frequency rated value	
<ul style="list-style-type: none"> minimum maximum 	50 Hz 60 Hz
operational current	
<ul style="list-style-type: none"> for circuit 1 at AC at 50 Hz rated value maximum for circuit 1 at AC at 60 Hz rated value maximum 	800 A 800 A
Mechanical Design	
height	700 mm
width	90 mm
length	650 mm
fastening method	ceiling / wall
Net Weight	27.09 kg
material of the busbar	aluminium
Approvals Certificates	
General Product Approval	



Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8PS6234-6TH08>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8PS6234-6TH08>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PS6234-6TH08
- CAx-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications
<http://www.siemens.com/specifications>

last modified:

7/1/2021

